

NASA  
Technical  
Memorandum

NASA TM - 103506

**HUBBLE SPACE TELESCOPE SIX-BATTERY TEST BED**

By J.A. Pajak, J.R. Bush, Jr., and J.R. Lanier, Jr.

Information and Electronic Systems Laboratory  
Science and Engineering Directorate

August 1990

(NASA-TM-103506) HUBBLE SPACE TELESCOPE  
SIX-BATTERY TEST BED (NASA) 99 n CSCL 14B

N90-27731

Unclassified  
G3/14 0303923



National Aeronautics and  
Space Administration

**George C. Marshall Space Flight Center**





## Report Documentation Page

1. Report No. <b>NASA TM - 103506</b>	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle <b>Hubble Space Telescope Six-Battery Test Bed</b>		5. Report Date <b>August 1990</b>	
7. Author(s) <b>JA. Pajak, J.R. Bush, Jr., and J.R. Lanier, Jr.</b>		6. Performing Organization Code	
9. Performing Organization Name and Address <b>George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812</b>		8. Performing Organization Report No.	
12. Sponsoring Agency Name and Address <b>National Aeronautics and Space Administration Washington, DC 20546</b>		10. Work Unit No.	
15. Supplementary Notes <p>Prepared by Information and Electronic Systems Laboratory, Science and Engineering Directorate</p>		11. Contract or Grant No.	
16. Abstract <p>A test bed for a large space power system breadboard for the Hubble Space Telescope (HST) was designed and built to test the system under simulated orbital conditions. A discussion of the data acquisition and control subsystems designed to provide for continuous 24-hour per day operation and a general overview of the test bed is presented. The data acquisition and control subsystems provided the necessary monitoring and protection to assure safe shutdown with protection of test articles in case of loss of power or equipment failure over the life of the test (up to 5 years).</p>		13. Type of Report and Period Covered <b>Technical Memorandum</b>	
17. Key Words (Suggested by Author(s)) <b>space power system testing, HST power system, HST power system test bed, battery testing, nickel-cadmium testing</b>		18. Distribution Statement <b>Unclassified – Unlimited</b>	
19. Security Classif. (of this report) <b>Unclassified</b>	20. Security Classif. (of this page) <b>Unclassified</b>	21. No. of pages <b>103</b>	22. Price <b>NTIS</b>



## TABLE OF CONTENTS

	Page
BACKGROUND .....	1
PURPOSE .....	1
SYSTEM CONFIGURATION .....	1
CHAMBER AND BATTERY PHYSICAL CONFIGURATION .....	2
TEST CONTROL AND DATA ACQUISITION .....	2
SOLAR ARRAY SIMULATORS.....	3
LOAD BUSES .....	3
CHARGE CURRENT CONTROLLER .....	3
CONTROL COMPUTER .....	4
TEST SHUTDOWN AND FAILURE PROTECTION.....	4
APPENDIX A – Analog Signals.....	19
APPENDIX B – Digital Inputs.....	29
APPENDIX C – Digital Outputs.....	31
APPENDIX D – Test Operations Program With Comments.....	33
APPENDIX E – Interrupt Handler Routine .....	65

## LIST OF ILLUSTRATIONS

Figure	Title	Page
1.	HST power system .....	5
2.	Test bed block diagram.....	6
3.	Chamber physical layout .....	7
4.	Installed batteries.....	8
5.	DAS system block diagram .....	9
6.	Single battery control circuit.....	10
7.	CPU/memory board .....	11
8.	Input/output board.....	12
9.	Analog interface board.....	13
10.	CCC trip sense and power supply control boards XB4 and XB5 .....	14
11.	Orbital summary data .....	15
12.	Failure conditions and scan data requests .....	16

## LIST OF TABLES

Table	Title	Page
1.	Data types read by the DAS .....	17
2.	Fault conditions.....	17

## **TECHNICAL MEMORANDUM**

### **HUBBLE SPACE TELESCOPE SIX-BATTERY TEST BED**

#### **BACKGROUND**

A power system test bed has been developed to test the Hubble Space Telescope (HST) power system using nickel-cadmium (Ni-Cd) batteries. The test bed provides orbital simulation for charging and discharging the batteries under various operational configurations. Orbital sequencing and data acquisition is accomplished by the data acquisition system (DAS) with solar array simulation (SAS) and load sequencing controlled by the control computer (CC).

The test bed provides space and control for a six-battery power system configuration. The batteries are assembled from Eagle-Picher type 44 Ni-Cd cells, assembled in flight type cases and incorporate battery protection and reconditioning circuits (BPRC).

Test operations are designed for continuous, unattended, operations 24 hours a day, 365 days a year. This type of long term operation (3 to 5 years) requires special considerations for accumulation of data, failure protection, and protection of the test articles and supporting equipment.

#### **PURPOSE**

The HST six-battery Ni-Cd test bed was designed to provide a testing facility for the HST power system flight configuration. Testing operations were designed to simulate the HST power operations at liftoff, solar array deployment, orbital insertion, and in-orbit operations. The facility also simulates battery environment temperatures. Data collection and subsequent analysis require large volumes of data for trend analysis and anomaly investigation.

#### **SYSTEM CONFIGURATION**

A diagram of the HST flight operating system is shown in figure 1. Figure 2 is a block diagram of the test bed. Total duplication of the flight system is, of course, impossible, but every attempt was made to duplicate flight operations on the batteries and their operation in the system. Certain modifications were made to the physical battery configuration to allow insertion in an environmental chamber and for additional nonflight instrumentation, such as cell pressures, cell voltages, and additional temperature measurements. The test bed is located in building 4475, rooms 139 and 140. The test bed configuration design also includes provisions for real-time, real-data transmission to an expert system development test bed (NICBES).

## CHAMBER AND BATTERY PHYSICAL CONFIGURATION

The environmental chamber employed in a test bed has a 64 ft<sup>3</sup> (4x4x4 ft) operating space with a conditioned gas inlet at the bottom rear and an exhaust outlet at the top rear. The chamber is purged with dry nitrogen as the environmental medium. The nitrogen reduces the likelihood of condensation during operation and when the chamber must be opened for test bed repairs or reconfiguration of physical devices. The nitrogen is under a slight positive pressure and is vented to the outside of the building. The chamber is easily capable of maintaining a set temperature in the operating range of -10 °C to 30 °C with a 1-kW heating load.

The batteries are divided into two groups of three batteries. Each of the battery groups is mounted on a cold plate. The cold plates have imbedded heaters to allow separate control of the battery group temperatures. The cold plates, with batteries, are stacked vertically in a support frame. Insulation surrounds the battery groups on top, sides, and ends to force most generated heat to be extracted via the cold plates. Baffling exists in the chamber to direct the circulating ambient environment to the cold plates for proper heat transfer. The battery physical arrangement thus provides a thermal path similar to that expected in space operation.

A physical modification to the battery cases has been made to accommodate the individual cell pressure transducers and their attendant cabling and to allow wiring to each cell terminal to obtain cell voltages. This modification is accomplished by using 1-inch spacers between the battery case and lid. The lid is still within the insulation surrounding the groups for thermal integrity.

Figure 3 is a depiction of the chamber physical layout. Figure 4 is a photograph of the installed batteries.

## TEST CONTROL AND DATA ACQUISITION

Signals from the DAS control the orbital day/night time of the test bed. Day/night orbital times are synchronized with the DAS 1-min scan rate to preclude data acquisition during the battery charge-discharge transitions, and to allow stabilization of operating parameters between readings. The DAS also performs limit checking on the data to alert to failure conditions of support equipment such as environmental chamber cooling failure, building power failure, SAS equipment failure, and cell-battery failure.

Table 1 lists the types and distribution of data types read by the DAS, while appendices A through C list the channel assignments. The DAS is a system assembled by DSP Inc. utilizing a LSI-11/23 DEC board computer as the processor. The operating system is RT-11 with the operating programs written in BASIC for ease of modification and interactive operator control. Data scanning is accomplished using 16-channel, flying-capacitor, reed-relay multiplexors. Network completion circuits are also provided for resistance measurements of thermistor temperature circuits.

Figure 5 is a block diagram of the DAS system. A typical control circuit for a single battery is shown in figure 6.

The DAS also incorporates a switch panel to provide operator control of scan data printouts, recycling of orbital position to the beginning of day or night (start of new orbit), and forcing discharge during day or charge during night phase.

To accommodate the accumulation and retention of large amounts of data (370 items per scan), an external "AT" class computer has been attached to a RS232 port. This computer incorporates an optical disk of the "write once-read many" (WORM) technology. Two hundred mega-bytes of storage are available per disk. This represents about 3 weeks of data. This same data is also routed to an expert system test bed for real-time development of artificial intelligence (AI) technologies as applied to large space power systems.

The DAS also has two printer outputs. One printer is used for listing orbital summary data (fig. 11) and the second printer lists failure conditions and scan data requests (fig. 12).

Appendix D is the control and data acquisition program for the LSI-11/23 with comments added for clarity. Also included are the DAS operating instructions.

## **SOLAR ARRAY SIMULATORS**

The HST orbital configuration consists of 20 solar panels divided into groups of 3 panels for each battery, with the remaining 2 panels connected directly to bus C. For test simulation, two power supplies per battery are employed. One power supply (type 1) of the pair simulates a single solar panel, the second supply (type 2) simulates the output of two solar panels. The SAS control circuits can thus simulate the power delivered by type 1, 2, or 3 panels, as determined by the charge current controllers (CCC). A type 2 supply simulates the two solar power arrays (SPA's) connected to bus C.

## **LOAD BUSES**

The HST three-flight load buses are replicated by three programmable load banks. Each load bank is independently controlled by the CC to perform in the predicted orbital configuration, including the failure SAFEMODE.

## **CHARGE CURRENT CONTROLLER**

The charge voltage of each battery is controlled by a CCC. Each CCC controls the number and battery cut-off voltages of the SPA's (SAS) charging each battery. The cutoff voltages are temperature compensated to reduce charging stress at higher temperatures.

## **CONTROL COMPUTER**

The control computer is an inhouse designed and fabricated microprocessor system. The CC has an operator interface for entry of desired orbital operating parameters. A TI 9900 chip is used as the central processing unit (CPU) with series supporting chips and 2k bytes of EPROM memory. The CC provides for independent SAS control (simulating HST orientation and SPA degradation), load bank control (simulating various load conditions), and monitoring of CCC operation, battery temperature, battery voltage, and DAS operation. The CC circuits also provide failure monitoring of the SAS and CCC. The CC incorporates a 16-channel multiplexor and 12-bit analog/digital (A/D) converter for analog data monitoring. CC output control is accomplished via two 16-bit I/O chips with relay driver interface. The CC logic and board circuitry are shown in figures 7 through 10.

The CC operating program is programmed into the EPROM memory. Appendix E is a listing of the two programs for CC operation and operator interface.

## **TEST SHUTDOWN AND FAILURE PROTECTION**

The number of individual subsystems and integrated operation of the test bed requires several levels of failure protection and test shutdown. Since the test bed is earthbound and dependent on utility power for operations, an uninterruptable power source supplies the operating power for the DAS and CC. Since the test bed is designed for continuous, unattended, operation all circuits have FAIL-SAFE provisions, and the DAS and CC are connected to an autodialer circuit to notify test personnel of a failure night or day.

Protection of the test articles (batteries) and the test bed equipment is an important consideration, therefore the conditions listed in table 2 are considered faults and initiate the indicated actions. Test shutdown for failures requires operator intervention for restart, even if the fault self corrects. This is a safety precaution to verify that the fault cause is found and properly cleared or corrected.




Figure 1. HST power system.




Figure 2. Test bed block diagram.




Figure 3. Chamber physical layout.

**ORIGINAL PAGE  
BLACK AND WHITE PHOTOGRAPH**




Figure 4. Installed batteries.





Figure 5. DAS system block diagram.

ORIGINAL PAGE IS  
OF POOR QUALITY

Figure 6. Single battery control circuit.



ORIGINAL PAGE IS  
OF POOR QUALITY




Figure 7. CPU/memory board.




Figure 8. Input/output board.




Figure 9. Analog interface board.




Figure 10. CCC trip sense and power supply control boards XB4 and XB5.

BAT	ORBIT	SUNSET TIME	BAT WHO	BAT EFF	DCH	CHG	RR	DDD	AHO	BFRIC AH	CHI	T-CAV	T-CLO	T--DHI	T-DAV	T-DLO	T		
1	9700	1988: 53:23:12: 0	276.1	0.919	36	56	1.016	16.83	9.15	0.11	9.31	9.42	9.34	11.16	10.75	10.77			
	DHI	CV--CNO--AV	CV--DLO	CV--CNO			CHI	CV--CNO--AV	CV--CLO	CV--CNO				HI PRESS--CNO	DODD	SOC	SOD	TTT RRAV	
	1.256	12	1.254	1.251	?		1.449	14	1.444	1.438	7			6.0	5	-0.11	49.06	39.81	39 1.009
	BAT	ORBIT	SUNSET TIME	BAT WHO	BAT EFF	DCH	CHG	RR	DDD	AHO	BFRIC AH	CHI	T-CAV	T-CLO	T--DHI	T-DAV	T-DLO	T	
2	9700	1988: 53:23:12: 0	253.0	0.908	36	56	1.026	15.34	8.44	0.11	9.39	9.09	8.83	10.71	10.31	10.37			
	DHI	CV--CNO--AV	CV--DLO	CV--CNO			CHI	CV--CNO--AV	CV--CLO	CV--CNO				HI PRESS--CNO	DODD	SOC	SOD	TTT RRAV	
	1.254	21	1.245	1.240	8		1.460	14	1.451	1.425	21			11.2	18	-0.27	48.84	40.40	39 1.025
	BAT	ORBIT	SUNSET TIME	BAT WHO	BAT EFF	DCH	CHG	RR	DDD	AHO	BFRIC AH	CHI	T-CAV	T-CLO	T--DHI	T-DAV	T-DLO	T	
3	9700	1988: 53:23:12: 0	265.6	0.915	36	56	1.018	17.28	9.50	0.09	9.21	9.10	9.00	10.94	10.65	10.41			
	DHI	CV--CNO--AV	CV--DLO	CV--CNO			CHI	CV--CNO--AV	CV--CLO	CV--CNO				HI PRESS--CNO	DODD	SOC	SOD	TTT RRAV	
	1.257	13	1.252	1.248	14		1.451	1	1.446	1.439	6			6.9	7	-0.13	49.31	39.80	39 1.010
	BAT	ORBIT	SUNSET TIME	BAT WHO	BAT EFF	DCH	CHG	RR	DDD	AHO	BFRIC AH	CHI	T-CAV	T-CLO	T--DHI	T-DAV	T-DLO	T	
4	9700	1988: 53:23:12: 0	241.0	0.898	36	56	1.040	14.62	8.04	0.10	11.64	11.54	11.49	12.85	12.73	11.51			
	DHI	CV--CNO--AV	CV--DLO	CV--CNO			CHI	CV--CNO--AV	CV--CLO	CV--CNO				HI PRESS--CNO	DODD	SOC	SOD	TTT RRAV	
	1.255	23	1.245	1.240	14		1.460	7	1.449	1.427	8			12.1	12	-0.43	48.80	40.75	39 1.032
	BAT	ORBIT	SUNSET TIME	BAT WHO	BAT EFF	DCH	CHG	RR	DDD	AHO	BFRIC AH	CHI	T-CAV	T-CLO	T--DHI	T-DAV	T-DLO	T	
6	9700	1988: 53:23:12: 0	238.8	0.899	36	56	1.040	14.47	7.96	0.09	10.35	10.15	9.85	11.68	11.31	10.64			
	DHI	CV--CNO--AV	CV--DLO	CV--CNO			CHI	CV--CNO--AV	CV--CLO	CV--CNO				HI PRESS--CNO	DODD	SOC	SOD	TTT RRAV	
	1.264	11	1.244	1.232	5		1.460	19	1.452	1.441	11			20.5	20	-0.43	48.57	40.62	39 1.036

Figure 11. Orbital summary data.

1986 : 107 : 12 : 22 : 0 ORB= 202 P= 1 C2= 22 C4= 1

BATTERY= 1 V= 32.2453 I= 5.995 BPRC I= .057375

1.3996	1.3991	1.3999	1.4016	1.4003	1.3986	1.4000	1.4026	1.4010	1.4006	1.3992	1.3992
1.3999	1.4013	1.3998	1.4019	1.4006	1.4025	1.4013	1.4017	1.3999	1.4050	1.4000	
-1.70	-1.76	-1.79	-1.87	-1.91	-1.73						
6.21	0.39	-8.54	3.11	-0.78	-8.93	-1.55	-6.60	-0.78	-3.49	1.55	7.38
0.78	-6.60	-3.11	-4.66	-3.49	-1.94	-5.82	-9.71	-4.27	3.49	-0.39	

BATTERY= 2 V= 32.264 I= 5.9925 BPRC I= .064

T:4009	1.4016	1.4010	1.4013	1.4009	1.4002	1.3999	1.4011	1.4004	1.4005	1.3995	1.3999
1.3999	1.4014	1.4020	1.3995	1.3991	1.4012	1.4013	1.4005	1.4002	1.3998	1.3998	
-1.70	-1.54	-1.68	-1.78	-1.76	-1.70						
-6.99	-11.65	-1.94	12.04	-3.11	-0.39	-6.21	-0.39	-4.66	1.94	-10.87	-5.44
-15.53	-6.60	0.00	5.82	-0.39	-8.15	-15.53	-0.39	-5.82	2.72	-3.11	

BATTERY= 3 V= 32.2578 I= 5.9395 BPRC I= .0495

1.4012	1.3999	1.4006	1.4009	1.3999	1.4012	1.4012	1.4009	1.3993	1.3999	1.4001	1.3998
1.3997	1.3990	T:4013	1.4006	1.4006	1.3998	1.4006	1.4020	1.4004	1.3999	1.3999	
-1.62	-1.95	-1.72	-1.58	-1.61	-1.60						
-11.26	2.33	0.00	12.43	-6.21	-2.72	-0.99	31.00	-2.39	0.00	-6.99	0.00
-9.71	6.60	6.21	-37.28	-6.99	0.00	-3.49	6.21	0.39	-2.72	-1.55	

BATTERY= 4 V= 32.2766 I= 6.004 BPRC I= .059875

1.4021	1.4007	1.3999	1.3999	1.4009	1.4002	1.4001	1.4016	1.4010	1.4024	1.4020	1.4001
1.4019	1.4015	1.3998	1.4012	1.4026	1.4019	1.4025	1.4012	1.4027	1.4009	1.3999	
-1.55	-1.38	-1.61	-1.76	-1.35	-1.43						
-6.21	-1.16	-1.94	0.39	0.00	-8.54	-6.21	-4.27	-6.60	-1.16	-3.49	0.39
-0.39	-1.94	-12.81	-2.72	-0.39	-1.55	-5.05	-8.15	-12.81	-1.16	-0.39	

BATTERY= 5 V= 32.2453 I= 6.0025 BPRC I= .07025

1.3998	1.4006	1.3994	1.4000	1.3988	1.3998	1.3996	1.3997	1.3994	1.3994	1.3984	1.3988
1.4000	1.3993	1.4008	1.3994	1.4006	1.3999	1.4002	1.3993	1.4013	1.3994	1.4030	
-1.77	-1.83	-1.87	-1.96	-1.90	-1.86						
-8.60	6.21	0.00	-11.65	13.98	0.00	-3.11	-2.72	-2.72	-7.38	-5.44	-3.11
-7.38	1.16	4.27	-5.82	-5.44	-5.82	-9.71	-11.65	-1.55	7.38	0.00	

Figure 12. Failure conditions and scan data requests.

Table 1. Data types read by the DAS.

<u>DAS channels</u>	<u>type of signal</u>	<u>Quan.</u>	<u>Use</u>
<b>ANALOG</b>			
0-255	0-+/- 2.4 v	256	cell volt. and cell press.
256-335	0-+/- 2.4 v	80	same as above
336-375	0-100k ohms	40	theristor temperature
376-399	0-200 v	24	battery and load volts.
400-415	0-+/- 100 mv	16	battery and SAS curr.
<b>DIGITAL</b>			
0-63	TTL level	64	cc contol
0-15	switches	16	alarm and level control
0-15	28 v level	16	operator control panel
16-31	TTL level	16	battery status

Table 2. Fault conditions.

<u>Fault</u>	<u>Action</u>
Environmental chamber temp. too high	Shutdown
Environmental chamber temp. too low	Shutdown
SAS current too high	Alarm
DAS not scanning	Shutdown
Cell voltage too high	Shutdown
Cell voltage too low	Shutdown
Bus current too high	Shutdown
SAS curr. too low at start of charge	Alarm
Utility power failure	Alarm



**Appendix A**  
**ANALOG SIGNALS**

Channel	Use	Voltage (Volts) (+ or -)
0	Batt 1 / Cell 1	2.5
1	Batt 1 / Cell 2	
2	Batt 1 / Cell 3	
3	Batt 1 / Cell 4	
4	Batt 1 / Cell 5	
5	Batt 1 / Cell 6	
6	Batt 1 / Cell 7	
7	Batt 1 / Cell 8	
8	Batt 1 / Cell 9	
9	Batt 1 / Cell 10	
10	Batt 1 / Cell 11	
11	Batt 1 / Cell 12	
12	Batt 1 / Cell 13	
13	Batt 1 / Cell 14	
14	Batt 1 / Cell 15	
15	Batt 1 / Cell 16	
16	Batt 1 / Cell 17	
17	Batt 1 / Cell 18	
18	Batt 1 / Cell 19	
19	Batt 1 / Cell 20	
20	Batt 1 / Cell 21	
21	Batt 1 / Cell 22	
22	Batt 1 / Cell 23	
23	Batt 2 / Cell 1	
24	Batt 2 / Cell 2	
25	Batt 2 / Cell 3	
26	Batt 2 / Cell 4	
27	Batt 2 / Cell 5	
28	Batt 2 / Cell 6	
29	Batt 2 / Cell 7	
30	Batt 2 / Cell 8	
31	Batt 2 / Cell 9	
32	Batt 2 / Cell 10	
33	Batt 2 / Cell 11	
34	Batt 2 / Cell 12	
35	Batt 2 / Cell 13	
36	Batt 2 / Cell 14	
37	Batt 2 / Cell 15	
38	Batt 2 / Cell 16	
39	Batt 2 / Cell 17	
40	Batt 2 / Cell 18	
41	Batt 2 / Cell 19	
42	Batt 2 / Cell 20	
43	Batt 2 / Cell 21	
44	Batt 2 / Cell 22	
45	Batt 2 / Cell 23	2.5
46		

~~18~~ INTENTIONALLY BLANK

**Appendix A cont.**

<b>Channel</b>	<b>Use</b>	<b>Voltage (Volts)</b> <b>(+ or -)</b>
47	Batt 3 / Cell 1	2.5
48	Batt 3 / Cell 2	
49	Batt 3 / Cell 3	
50	Batt 3 / Cell 4	
51	Batt 3 / Cell 5	
52	Batt 3 / Cell 6	
53	Batt 3 / Cell 7	
54	Batt 3 / Cell 8	
55	Batt 3 / Cell 9	
56	Batt 3 / Cell 10	
57	Batt 3 / Cell 11	
58	Batt 3 / Cell 12	
59	Batt 3 / Cell 13	
60	Batt 3 / Cell 14	
61	Batt 3 / Cell 15	
62	Batt 3 / Cell 16	
63	Batt 3 / Cell 17	
64	Batt 3 / Cell 18	
65	Batt 3 / Cell 19	
66	Batt 3 / Cell 20	
67	Batt 3 / Cell 21	
68	Batt 3 / Cell 22	
69	Batt 3 / Cell 23	
70	Batt 4 / Cell 1	
71	Batt 4 / Cell 2	
72	Batt 4 / Cell 3	
73	Batt 4 / Cell 4	
74	Batt 4 / Cell 5	
75	Batt 4 / Cell 6	
76	Batt 4 / Cell 7	
77	Batt 4 / Cell 8	
78	Batt 4 / Cell 9	
79	Batt 4 / Cell 10	
80	Batt 4 / Cell 11	
81	Batt 4 / Cell 12	
82	Batt 4 / Cell 13	
83	Batt 4 / Cell 14	
84	Batt 4 / Cell 15	
85	Batt 4 / Cell 16	
86	Batt 4 / Cell 17	
87	Batt 4 / Cell 18	
88	Batt 4 / Cell 19	
89	Batt 4 / Cell 20	
90	Batt 4 / Cell 21	
91	Batt 4 / Cell 22	
92	Batt 4 / Cell 23	2.5

**Appendix A cont.**

Channel	Use	Voltage (Volts) (+ or -)
93	Batt 5 / Cell 1	2.5
94	Batt 5 / Cell 2	
95	Batt 5 / Cell 3	
96	Batt 5 / Cell 4	
97	Batt 5 / Cell 5	
98	Batt 5 / Cell 6	
99	Batt 5 / Cell 7	
100	Batt 5 / Cell 8	
101	Batt 5 / Cell 9	
102	Batt 5 / Cell 10	
103	Batt 5 / Cell 11	
104	Batt 5 / Cell 12	
105	Batt 5 / Cell 13	
106	Batt 5 / Cell 14	
107	Batt 5 / Cell 15	
108	Batt 5 / Cell 16	
109	Batt 5 / Cell 17	
110	Batt 5 / Cell 18	
111	Batt 5 / Cell 19	
112	Batt 5 / Cell 20	
113	Batt 5 / Cell 21	
114	Batt 5 / Cell 22	
115	Batt 5 / Cell 23	
116	Batt 6 / Cell 1	
117	Batt 6 / Cell 2	
118	Batt 6 / Cell 3	
119	Batt 6 / Cell 4	
120	Batt 6 / Cell 5	
121	Batt 6 / Cell 6	
122	Batt 6 / Cell 7	
123	Batt 6 / Cell 8	
124	Batt 6 / Cell 9	
125	Batt 6 / Cell 10	
126	Batt 6 / Cell 11	
127	Batt 6 / Cell 12	
128	Batt 6 / Cell 13	
129	Batt 6 / Cell 14	
130	Batt 6 / Cell 15	
131	Batt 6 / Cell 16	
132	Batt 6 / Cell 17	
133	Batt 6 / Cell 18	
134	Batt 6 / Cell 19	
135	Batt 6 / Cell 20	
136	Batt 6 / Cell 21	
137	Batt 6 / Cell 22	2.5

**Appendix A cont.**

Channel	Use	Voltage (Volts) (+ or -)
138	Batt 6 / Cell 23	2.5
139	Not Used	
140	Not Used	
141	Batt 1 / Cell 1 Press	
142	Batt 1 / Cell 2 Press	
143	Batt 1 / Cell 3 Press	
144	Batt 1 / Cell 4 Press	
145	Batt 1 / Cell 5 Press	
146	Batt 1 / Cell 6 Press	
147	Batt 1 / Cell 7 Press	
148	Batt 1 / Cell 8 Press	
149	Batt 1 / Cell 9 Press	
150	Batt 1 / Cell 10 Press	
151	Batt 1 / Cell 11 Press	
152	Batt 1 / Cell 12 Press	
153	Batt 1 / Cell 13 Press	
154	Batt 1 / Cell 14 Press	
155	Batt 1 / Cell 15 Press	
156	Batt 1 / Cell 16 Press	
157	Batt 1 / Cell 17 Press	
158	Batt 1 / Cell 18 Press	
159	Batt 1 / Cell 19 Press	
160	Batt 1 / Cell 20 Press	
161	Batt 1 / Cell 21 Press	
162	Batt 1 / Cell 22 Press	
163	Batt 1 / Cell 23 Press	
164	Batt 2 / Cell 1 Press	
165	Batt 2 / Cell 2 Press	
166	Batt 2 / Cell 3 Press	
167	Batt 2 / Cell 4 Press	
168	Batt 2 / Cell 5 Press	
169	Batt 2 / Cell 6 Press	
170	Batt 2 / Cell 7 Press	
171	Batt 2 / Cell 8 Press	
172	Batt 2 / Cell 9 Press	
173	Batt 2 / Cell 10 Press	
174	Batt 2 / Cell 11 Press	
175	Batt 2 / Cell 12 Press	
176	Batt 2 / Cell 13 Press	
177	Batt 2 / Cell 14 Press	
178	Batt 2 / Cell 15 Press	
179	Batt 2 / Cell 16 Press	
180	Batt 2 / Cell 17 Press	
181	Batt 2 / Cell 18 Press	
182	Batt 2 / Cell 19 Press	
183	Batt 2 / Cell 20 Press	2.5

**Appendix A cont.**

Channel	Use	Voltage (Volts) (+ or -)
184	Batt 2 / Cell 21 Press	2.5
185	Batt 2 / Cell 22 Press	
186	Batt 2 / Cell 23 Press	
187	Batt 3 / Cell 1 Press	
188	Batt 3 / Cell 2 Press	
189	Batt 3 / Cell 3 Press	
190	Batt 3 / Cell 4 Press	
191	Batt 3 / Cell 5 Press	
192	Batt 3 / Cell 6 Press	
193	Batt 3 / Cell 7 Press	
194	Batt 3 / Cell 8 Press	
195	Batt 3 / Cell 9 Press	
196	Batt 3 / Cell 10 Press	
197	Batt 3 / Cell 11 Press	
198	Batt 3 / Cell 12 Press	
199	Batt 3 / Cell 13 Press	
200	Batt 3 / Cell 14 Press	
201	Batt 3 / Cell 15 Press	
202	Batt 3 / Cell 16 Press	
203	Batt 3 / Cell 17 Press	
204	Batt 3 / Cell 18 Press	
205	Batt 3 / Cell 19 Press	
206	Batt 3 / Cell 20 Press	
207	Batt 3 / Cell 21 Press	
208	Batt 3 / Cell 22 Press	
209	Batt 3 / Cell 23 Press	
210	Batt 4 / Cell 1 Press	
211	Batt 4 / Cell 2 Press	
212	Batt 4 / Cell 3 Press	
213	Batt 4 / Cell 4 Press	
214	Batt 4 / Cell 5 Press	
215	Batt 4 / Cell 6 Press	
216	Batt 4 / Cell 7 Press	
217	Batt 4 / Cell 8 Press	
218	Batt 4 / Cell 9 Press	
219	Batt 4 / Cell 10 Press	
220	Batt 4 / Cell 11 Press	
221	Batt 4 / Cell 12 Press	
222	Batt 4 / Cell 13 Press	
223	Batt 4 / Cell 14 Press	
224	Batt 4 / Cell 15 Press	
225	Batt 4 / Cell 16 Press	
226	Batt 4 / Cell 17 Press	
227	Batt 4 / Cell 18 Press	
228	Batt 4 / Cell 19 Press	
229	Batt 4 / Cell 20 Press	2.5

**Appendix A cont.**

Channel	Use	Voltage (Volts) (+ or -)
230	Batt 4 / Cell 21 Press	2.5
231	Batt 4 / Cell 22 Press	
232	Batt 4 / Cell 23 Press	
233	Batt 5 / Cell 1 Press	
234	Batt 5 / Cell 2 Press	
235	Batt 5 / Cell 3 Press	
236	Batt 5 / Cell 4 Press	
237	Batt 5 / Cell 5 Press	
238	Batt 5 / Cell 6 Press	
239	Batt 5 / Cell 7 Press	
240	Batt 5 / Cell 8 Press	
241	Batt 5 / Cell 9 Press	
242	Batt 5 / Cell 10 Press	
243	Batt 5 / Cell 11 Press	
244	Batt 5 / Cell 12 Press	
245	Batt 5 / Cell 13 Press	
246	Batt 5 / Cell 14 Press	
247	Batt 5 / Cell 15 Press	
248	Batt 5 / Cell 16 Press	
249	Batt 5 / Cell 17 Press	
250	Batt 5 / Cell 18 Press	
251	Batt 5 / Cell 19 Press	
252	Batt 5 / Cell 20 Press	
253	Batt 5 / Cell 21 Press	
254	Batt 5 / Cell 22 Press	
255	Batt 5 / Cell 23 Press	
256	Batt 6 / Cell 1 Press	
257	Batt 6 / Cell 2 Press	
258	Batt 6 / Cell 3 Press	
259	Batt 6 / Cell 4 Press	
260	Batt 6 / Cell 5 Press	
261	Batt 6 / Cell 6 Press	
262	Batt 6 / Cell 7 Press	
263	Batt 6 / Cell 8 Press	
264	Batt 6 / Cell 9 Press	
265	Batt 6 / Cell 10 Press	
266	Batt 6 / Cell 11 Press	
267	Batt 6 / Cell 12 Press	
268	Batt 6 / Cell 13 Press	
269	Batt 6 / Cell 14 Press	
270	Batt 6 / Cell 15 Press	
271	Batt 6 / Cell 16 Press	
272	Batt 6 / Cell 17 Press	
273	Batt 6 / Cell 18 Press	
274	Batt 6 / Cell 19 Press	
275	Batt 6 / Cell 20 Press	2.5

**Appendix A cont.**

<b>Channel</b>	<b>Use</b>	<b>Voltage (Volts)</b> <b>(+ or -)</b>
276	Batt 6 / Cell 21 Press	2.5
277	Batt 6 / Cell 22 Press	
278	Batt 6 / Cell 23 Press	
279	Not used	
280		
281		
282		
283		
284		
285		
286		
287		
288		
289		
290		
291		
292		
293		
294		
295		
296		
297		
298		
299		
300		
301		
302		
303		
304		
305		
306		
307		
308		
309		
310		
311		
312		
313		
314		
315		
316	Not Used	2.5

**Appendix A cont.**

<b>Channel</b>	<b>Use</b>	<b>Voltage (Volts) (+ or -)</b>
317	Not Used	2.5
318	Not Used	
319	Not Used	
320	BUS 1 CURR	
321	BUS 2 CURR	
322	BUS 3 CURR	
323	SAS 1 CURR	
324	SAS 2 CURR	
325	SAS 3 CURR	
326	SAS 4 CURR	
327	SAS 5 CURR	
328	SAS 6 CURR	
329	SAS 7 CURR	
330	SAS 8 CURR	
331	SAS 9 CURR	
332	SAS 10 CURR	
333	SAS 11 CURR	
334	SAS 12 CURR	
335	SAS 13 CURR	2.5
336	Batt 1 / Temp 1	THERM
337	Batt 1 / Temp 2	
338	Batt 1 / Temp 3	
339	Batt 1 / Temp 4	
340	Batt 1 / Temp 5	
341	Batt 1 / Temp 6	
342	Batt 2 / Temp 1	
343	Batt 2 / Temp 2	
344	Batt 2 / Temp 3	
345	Batt 2 / Temp 4	
346	Batt 2 / Temp 5	
347	Batt 2 / Temp 6	
348	Batt 3 / Temp 1	
349	Batt 3 / Temp 2	
350	Batt 3 / Temp 3	
351	Batt 3 / Temp 4	
352	Batt 3 / Temp 5	
353	Batt 3 / Temp 6	
354	Batt 4 / Temp 1	
355	Batt 4 / Temp 2	
356	Batt 4 / Temp 3	
357	Batt 4 / Temp 4	
358	Batt 4 / Temp 5	
359	Batt 4 / Temp 6	
360	Batt 5 / Temp 1	
361	Batt 5 / Temp 2	
362	Batt 5 / Temp 3	
363	Batt 5 / Temp 4	THERM

**Appendix A cont.**

Channel	Use	Voltage (Volts)
364	Batt 5 / Temp 5	THERM
365	Batt 5 / Temp 6	
366	Batt 6 / Temp 1	
367	Batt 6 / Temp 2	
368	Batt 6 / Temp 3	
369	Batt 6 / Temp 4	
370	Batt 6 / Temp 5	
371	Batt 6 / Temp 6	
372	Not Used	
373	Not Used	
374	Not Used	
375	Not Used	THERM
376	Batt 1 / VOLT	200 V
377	Batt 2 / VOLT	
378	Batt 3 / VOLT	
379	Batt 4 / VOLT	
380	Batt 5 / VOLT	
381	Batt 6 / VOLT	
382	BUS 1 / VOLT	
383	BUS 2 / VOLT	
384	BUS 3 / VOLT	
385	Not Used	
386	Not Used	
387	Not Used	
388	Not Used	
389	Not Used	
390	Not Used	
391	Not Used	
392	Not Used	
393	Not Used	
394	Not Used	
395	Not Used	
396	Not Used	
397	Not Used	
398	Not Used	
399	Not Used	200 V
400	Batt 1 / CURR	$\pm 100$ MV
401	Batt 2 / CURR	
402	Batt 3 / CURR	
403	Batt 4 / CURR	
404	Batt 5 / CURR	
405	Batt 6 / CURR	
406	BPRC 1 / CURR	
407	BPRC 2 / CURR	
408	BPRC 3 / CURR	
409	BPRC 4 / CURR	
410	BPRC 5 / CURR	
411	BPRC 6 / CURR	$\pm 100$ MV



**Appendix B**  
**Digital inputs**

Channel	Type	Function
1	Isolated	POWER FAILURE
2	Isolated	PRT BATT 1
3	Isolated	PRT BATT 2
4	Isolated	PRT BATT 3
5	Isolated	PRT BATT 4
6	Isolated	PRT BATT 5
7	Isolated	PRT BATT 6
8	Isolated	BUS PNT
9	Isolated	TAPE OFF LINE
10	Isolated	
11	Isolated	
12	Isolated	FORCE DAY
13	Isolated	BEGIN NIGHT
14	Isolated	BEGIN DAY
15	Isolated	FORCE NIGHT
16	Isolated	Not Used
17	Nonisolated	
18	Nonisolated	RECONDITION BATT 1
19	Nonisolated	RECONDITION BATT 2
20	Nonisolated	RECONDITION BATT 3
21	Nonisolated	RECONDITION BATT 4
22	Nonisolated	RECONDITION BATT 5
23	Nonisolated	RECONDITION BATT 6
24	Nonisolated	
25	Nonisolated	
26	Nonisolated	
27	Nonisolated	1PPM
28	Nonisolated	TIME BCD 1
29	Nonisolated	TIME BCD 2
30	Nonisolated	TIME BCD 4
31	Nonisolated	TIME BCD 8
32	Nonisolated	Not Used



**Appendix C**  
**Digital outputs**

Channel	Type	Function
1-0	Isolated	Not Used
1-1		DAY
1-2		NIGHT
1-3		Not Used
1-4		
1-5		
1-6		
1-7		
1-8		
1-9		
1-10		
1-11		
1-12		
1-13		
1-14		
1-15	Isolated	ALARM ON
2-0	Nonisolated	Not Used
2-1		SCANNING
2-2		SCANNING
2-3		Not Used
2-4		
2-5		
2-6		
2-7		
2-8		
2-9		
2-10		
2-11		
2-12		
2-13		
2-14		
2-15		
2-16		
2-17		
2-18		
2-19		
2-20		
2-21		
2-22		
2-23		
2-24		
2-25		
2-26		
2-27		
2-28		
2-29		
2-30		
2-31	Nonisolated	Not Used

**Appendix C Cont.**  
**Digital Outputs**

<b>Channel</b>	<b>Type</b>	<b>Function</b>
2-32	Nonisolated	Not Used
2-33		
2-34		
2-35		
2-36		
2-37		
2-38		
2-39		
2-40		
2-41		
2-42		
2-43		
2-44		
2-45		
2-46		
2-47		
2-48		
2-49		
2-50		
2-51		
2-52		
2-53		
2-54		
2-55		
2-56		
2-57		
2-58		
2-59		
2-60		
2-61		1PPM RS
2-62		TIME OFF
2-63	Nonisolated	TIME ADV TIME HOLD

**APPENDIX D**

**HUBBLE SPACE TELESCOPE  
NICD 6 BATTERY SYSTEM  
TEST OPERATIONS PROGRAM WITH COMMENTS  
REVISED FEB 27, 1990**

## DATA ACQUISITION SYSTEM STARTUP PROCEDURE

1. DADS RACK MAIN POWER SWITCH "ON" (BOTTOM PANEL)
2. RESET EXTERNAL CLOCK (TOP PANEL) & PRESS "STOP" SWITCH
3. SET EXTERNAL CLOCK TO CURRENT DAY & TIME
4. START CLOCK
5. TURN ON VIDEO DISPLAY  
MESSAGE SHOULD READ: (AFTER BEEP)  
V14F1 TEST OK
6. TURN ON PRINTER A AND VERIFY IS "ON LINE"
7. TURN ON PRINTER B AND VERIFY IT IS "ON LINE"
8. CONNECT MODEM
9. TURN ON LOWER "CAMAC" CRATE
10. TURN ON UPPER "CAMAC" CRATE
11. TURN ON BACKPLANE POWER (SHORT RACK)  
ENABLE SWITCH "UP", LTC SWITCH "UP"
12. TURN ON MAG TAPE POWER SWITCH
13. PUT "TAPE OFF LINE" SWITCH UP (AUX PANEL)
14. INSERT DISK "A" INTO DRIVE "0" (LEFT)
15. INSERT DISK "B" INTO DRIVE "1" (RIGHT)
16. VERIFY VIDEO DISPLAY IS OK  
MESSAGE SHOULD READ:  
V14F1 TEST OK
17. DEPRESS "BOOT" SWITCH ON UPPER "CAMAC" CRATE
18. THE FOLLOWING WILL BE DISPLAYED  
(ENTER BOLDFACED DATA, DATA SHOWN ARE EXAMPLES ONLY)  
(BOLD LETTERS ARE OPERATOR RESPONSES)  
(<> INDICATES "RETURN" KEY)
  - D 56 = 5015
  - SET TT SCOPE
  - D56 = 0
  - INITIALIZE VMO:  
VMO INITIALIZE; ARE YOU SURE? Y <>
  - COPY DYO: RT11SJ.SYS VMO:  
FILES COPIED  
DYO:RT11SJ.SYS TO VMO:RT11SJ.SYS
  - COPY DYO:SWAP.SYS VMO:  
FILES COPIED  
DYO:SWAP.SYS TO VMO:SWAP.SYS
  - COPY DYO:TT.SYS VMO:  
FILES COPIED  
DYO:TT.SYS TO VMO:TT.SYS
  - COPY DYO:DY.SYS VMO:

FILES COPIED  
DYO:DY.SYS TO VMO:DY.SYS

- o COPY DYO:VM.SYS VMO:  
    FILES COPIED  
    DYO:VM.SYS TO VMO:VM.SYS
- o COPY DYO:MS.SYS VMO:  
    FILES COPIED  
    DYO:MS.SYS TO VMO:MS.SYS
- o COPY DYO:LS.SYS VMO:  
    FILES COPIED  
    DYO:LS.SYS TO VMO:LS.SYS
- o COPY DYO:NL.SYS VMO:  
    FILES COPIED  
    DYO:NL.SYS TO VMO:NL.SYS
- o COPY DYO:LT.SYS VMO:  
    FILES COPIED  
    DYO:LT.SYS TO VMO:LT.SYS
- o COPY DYO:TV.SYS VMO:  
    FILES COPIED  
    DYO:TV.SYS TO VMO:TV.SYS
- o COPY DYO:DIR.SYS VMO:  
    FILES COPIED  
    DYO:DIR.SYS TO VMO:DIR.SYS
- o COPY DYO:PIP.SYS VMO:  
    FILES COPIED  
    DYO:PIP.SYS TO VMO:PIP.SYS
- o COPY DYO:DUP.SAV VMO:  
    FILES COPIED  
    DYO:DUP.SAV TO VMO:DUP.SAV
- o COPY DYO:RESORC.SAV VMO:  
    FILES COPIED  
    DYO:RESORC.SAV TO VMO:RESORC.SAV
- o COPY DY1:INIT.BAS VMO:  
    FILES COPIED  
    DY1:INIT.BAS TO VMO:INIT.BAS
- o COPY DY1: MAINOP.BAS VMO:  
    FILES COPIED  
    DY1: MAINOP.BAS TO VMO:MAINOP.BAS
- o COPY DYO:BASIC0.SAV VMO:  
    FILES COPIED  
    DYO:BASIC0.SAV TO VMO:BASIC0.SAV
- o COPY DYO:STARTX.COM VMO:STARTS.COM
- o COPY BOOT VMO:RT11SJ.SYS VMO:
- o BOOT VMO:
- o RT-11SJ (S) V05-01
- o D 56 = 5015

- o SET LS FORM, WIDTH = 132
- o ASS LS LP
- o SET TT SCOPE
- o SET EDIT KED
- o D 56 = 0
- o DATE 2-APR-86 <>
- o TIME 8:17:54 <>

A.

o RUN BASICO <>  
BASIC-11/RT-11 V02-03  
OPTIONAL FUNCTIONS (ALL, NONE, OR INDIVIDUAL)? A <>  
READY

RUN INIT <>

CRATE 4 STATUS

E205 INSTALLED IN STATION 1  
E220 INSTALLED IN STATION 2  
E220 INSTALLED IN STATION 3  
E220 INSTALLED IN STATION 4  
E220 INSTALLED IN STATION 5  
E220 INSTALLED IN STATION 6  
E220 INSTALLED IN STATION 7  
E220 INSTALLED IN STATION 8  
E220 INSTALLED IN STATION 9  
E220 INSTALLED IN STATION 10  
E220 INSTALLED IN STATION 11  
E220 INSTALLED IN STATION 12  
E220 INSTALLED IN STATION 13  
E220 INSTALLED IN STATION 14  
E220 INSTALLED IN STATION 15  
E220 INSTALLED IN STATION 16  
E220 INSTALLED IN STATION 17

ENTER 1 TO CONTINUE

? 1 <>

CRATE 5 STATUS

E120 INSTALLED IN STATION 2  
E140 INSTALLED IN STATION 3

E140 INSTALLED IN STATION 4  
E140 INSTALLED IN STATION 5

E205 INSTALLED IN STATION 6  
E240 INSTALLED IN STATION 7  
E205 INSTALLED IN STATION 8  
E220 INSTALLED IN STATION 9  
E220 INSTALLED IN STATION 10  
E220 INSTALLED IN STATION 11  
E220 INSTALLED IN STATION 12  
E220 INSTALLED IN STATION 13  
E220 INSTALLED IN STATION 14  
E220 INSTALLED IN STATION 15  
E220 INSTALLED IN STATION 16  
E220 INSTALLED IN STATION 17  
ENTER 1 TO CONTINUE  
? 1 <>  
ENTER ORBIT COUNT  
? 1 <>  
ENTER CURRENT YEAR  
? 1986 <>  
ENTER DISCHARGE MIN.  
? 35 <>  
ENTER CHARGE MIN.  
? 60 <>  
ENTER ORBITS TO SKIP  
? 0 <>  
(DELAY TO NEXT LINE WILL BE APPROX 10 SEC.)  
STOP AT LINE 590  
(ANY SET UP CHANGES MAY BE MADE AT THIS POINT)  
(DISCH MIN = C3 = )  
(CHARGE MIN = C1 = )  
(SHUTDOWN FLAG = F9 = 0)  
(BATT'S 1,2,3 HI LIMIT = L1= )  
(BATT'S 4,5,6 HI LIMIT = L2= )  
(ALL BATT'S LO LIMIT = L8= )  
(ORBIT NO. = O1 = )  
(ORBITS TO SKIP = S1 = )

**GOTO 600 <>**  
(PROGRAM & SCANNING START WITH NIGHT [DISCHARGE] AND SCAN OF  
0)  
(THE FOLLOWING WILL BE DISPLAYED AFTER COMPLETION OF EACH  
SCAN)  
"DISCHARGE TIME 1 C3=35 ORBIT 1" OR "CHARGE TIME 1 C1=60  
ORBIT 1"  
AFTER CHECKING FOR TIME DISPLAY ABOVE, MAGNETIC TAPE MAY BE  
PUT ON LINE BY PUTTING "TAPE OFF LINE" SWITCH TO THE DOWN  
POSITION.

## VARIABLE DESCRIPTIONS

A =Average temperature in hi/lo subroutine.  
A1(6) =Amp-min in summation.  
A2(6) =Amp-min out summation.  
A3(6) =BPRC ahr summation.  
A6(6) =Orbit high pressure.  
A7(6) =Orbit high pressure cell no.  
A8(3) =Bus current.  
A9(3) =Bus voltage.

B1(6) =Discharge hi cell voltage.  
B2(6) =Discharge hi cell no.  
B3(6) =Discharge lo cell voltage.  
B4(6) =Discharge lo cell no.  
B5(6) =Discharge average cell voltage.  
B6(6) =Discharge battery voltage at lo cell.  
B7(7) =Discharge hi temperature.  
B8(6) =Discharge lo temperature.  
B9(6) =Discharge average temperature.

C1 =Charge time of orbit.  
C2 =Charge elapsed min. counter.  
C3 =Discharge time of orbit.  
C4 =discharge elapsed min. counter.  
C5(6) =Reconditioning counter.  
C8 =Print value of C2.  
C9 =Print value of C4.  
C\$ =";"

D1(6,23)=Cell voltage.  
D2(6) =Battery voltage.  
D3(6) =Battery current.  
D5(6) =Battery temperature.  
D6(13) =SAS/PS current.  
D7(6) =Last scan current.  
D8(6,23)=Cell pressure.  
D9(6) =BPRC current.

E1(6) =Charge hi cell voltage.  
E2(6) =Charge hi cell no.  
E3(6) =Charge lo cell voltage.  
E4(6) =Charge lo cell no.  
E5(6) =Charge average cell voltage.  
E6(6) =Charge battery volts at hi cell.  
E7(6) =Charge hi temperature.  
E8(6) =Charge lo temperature.  
E9(6) =Charge average temperature.

F1(0) =Dig. input, power fail.

```

F1(1) =Dig. input, battery 1 print request.
F1(2) =Dig. input, battery 2 print request.
F1(3) =Dig. input, battery 3 print request.
F1(4) =Dig. input, battery 4 print request.
F1(5) =Dig. input, battery 5 print request.
F1(6) =Dig. input, battery 6 print request.
F1(7) =Dig. input, bus data print request.
F1(8) =Dig. input, tape off line.
F1(9) =Dig. input, skip scan on mag. tape.
F1(10) =
F1(11) =Dig. input, force day.
F1(12) =Dig. input, begin night.
F1(13) =Dig. input, begin day.
F1(14) =Dig. input, force night.
F1(15) =bad
F2(0) =
F2(1) =Dig. input, reconditioning battery 1.
F2(2) =Dig. input, reconditioning battery 2.
F2(3) =Dig. input, reconditioning battery 3.
F2(4) =Dig. input, reconditioning battery 4.
F2(5) =Dig. input, reconditioning battery 5.
F2(6) =Dig. input, reconditioning battery 6.
F2(7) =Dig. input, trickle charge.
F2(8) =
F2(9) =
F2(10) =Dig. input, 1ppm log pulse.
F2(11) =Dig. input, time BCD 1.
F2(12) =Dig. input, time BCD 2.
F2(13) =Dig. input, time BCD 4.
F2(14) =Dig. input, time BCD 8.
F2(15) =bad
F3 =Roll flag.
F7 =SOC reset flag.
F8 =Discrete trickle flag.
F9 =Shutdown flag.

G1 =Temporary battery WHO for print.
G2 =Temporary battery EFF for print.
G3 =Temporary battery RR for print.
G4 =Temporary battery DCH or Dcc for print.
G5 =Temporary battery DOD for print.
G6 =Temporary battery AHO for print.
G7 =Temporary battery BPRC_WH for print.

H =Hi temperature in hi\lo temperature routine.

I =Temporary counter, usually battery no.
I1 =Temporary counter.

J =Temporary counter, usually cell no.
J1 =Temporary counter.

K1 =AHO constant (1/60).

```

L =Lo temperature in hi\lo temperature routine.  
 L1 =Battery 1,2,3 hi cell limit.  
 L2 =Battery 4,5,6 hi cell limit.  
 L8 =Battery lo limit.  
 L9 =Current cell limit in use.  
  
 M% =Multiplexor and ADC setup values.  
 M1 =Mag tape off line flag.  
  
 N =Temporary no. storage.  
 N1(9) =Temporary no. storage in time calc..  
  
 O1 =Orbit no.  
  
 P1 =Battery "printed" flag.  
 P2 =Phase flag, 0= disc.,1=chrg.  
 P3 =Forced night flag.  
 P4 =Forced day flag.  
 P5 =Printout phase flag  
 P8 =Flag to check P.S. during 1st 5 min of day.  
 P9 =Flag to check load during night.  
  
 R =Temporary resistor value.  
 R2 =Constant for DOD calc. (1.01)  
 R9(5,9) =RR from 10 orbits.  
  
 S1 =Orbits to skip value.  
 S2 =Skip counter.  
 S3 =Skip scan counter.  
 S4(6) =SOC max value.  
 S5(6) =SOC accumulative.  
 S6 =SOC print value.  
 S7(6) =SOD print value.  
  
 T1(4) =Storage for scan time.  
 T2(4) =Converted time characters.  
 T3(6,4) =Sunset time.  
 T9 =No. of scans on tape counter.  
  
 U1 =Print request counter.  
 U2 =Retry counter.  
  
 V =Temporary value in temperature calc.  
 V1 =Power fail flag.  
 V2 =First scan flag.  
 V3(6) =Reconditioning flag.  
 V4(6) =Capacity test complete flag.  
 V5(13) =SAS/PS failure flag.  
 V6(6) =Battery current failure flag.  
 V7 =Begin night flag.  
 V8 =Begin day flag.  
  
 W1(6) =Battery watt-min in summation.  
 W2(6) =Battery watt-min out summation.

**Z1%**      =ADC and switch reg. output values.  
**Z2%**      =Temporary output value.

WHERE TO CHANGE NON-VARIABLE LIMITS

LINE NO.	DESCRIPTION	CURRENT VALUE
565	SOC BASE VALUE	55
2700	BATT RECOND. 1ST LIMIT	26.45 (VOLTS)
3020	BATT. I UPPER LIMIT AT NIGHT	5 (AMPS)
4073	EXTRANEous CELL VOLTAGE DEVIATION BETWEEN SCANS (EXCEPT FIRST OF PHASE)	.01 (VOLTS)
4151	EXTRANEous CELL PRESS.	10 (PSI)
4241	DEVIATION	
4311	EXTRANEous BATT. V DEV.	.1 (VOLTS)
4390-4420	CORRECTION FACTORS FOR CURRENTS	
4490	BATT TEMP. O.C. VALUE	2.2303 (VOLTS)
4500	BATT. TEMP. SHRT. CIR.	-1.2575 (VOLTS)
7080	BATT. DISC. CURR. LIMIT	-30 (AMPS)
7090	BATT. CHRG. CURR. LIMIT	25 (AMPS)
7620	SAS P.S. DISC. LIMIT	5 (AMPS)
7830	SAS P.S. CHRG 5 MIN LIMIT	5 (AMPS)
8580	BATT. AVE. HI TEMP. LIMIT	30 (DEG. C)
8590	BATT. AVE. LO TEMP. LIMIT	-10 (DEG. C)

THIS SECTION IS THE FIRST PROGRAM GROUP AND WILL  
CHAIN TO THE MAIN OPERATING PROGRAM WHEN COMPLETE

```
1 REM "INIT" Routine to initialize crates and modules
  *Define the variables common to both program sections
50 COMMON O1,C3,C1,T1(4),S1
  *The next section initializes crate #4 and checks for
  *the module codes.
100 CALL CRATE(4) \ CALL INIT \ CALL INH(0)
  *Print status header
110 PRINT "CRATE 4 STATUS"
  *Set up module loop
120 FOR J=1 TO 17
  *Get module ID numbers
130 CALL C(J,0,1,I)
  *Print module ID no.
140 PRINT "E";I;" INSTALLED IN POSITION ";J
  Get another module ID
150 NEXT J
  *Print operator instruction
160 PRINT "ENTER 1 TO CONTINUE"
  *Get input
170 INPUT J1
  *Verify input is a 1
180 IF J1<>1 GOTO 160
  *The next part initializes crate #5 and checks
  *the ID of all modules
190 CALL CRATE(5) \ CALL INIT \ CALL INH(0)
  *Print status header
200 PRINT "CRATE 5 STATUS"
  *Set up module loop
210 FOR J=2 TO 17
  *Get module ID's
220 CALL C(J,0,1,I)
  *Print status
230 PRINT "E ";I;" INSTALLED IN POSITION ";J
  *Next module
240 NEXT J
  *Print instruction
250 PRINT "ENTER 1 TO CONTINUE"
  *Get input
260 INPUT J1
  *Verify input is a 1
270 IF J1<>1 GOTO 250
  *This section gets the starting orbit no. and year
  *Print instruction
280 PRINT "ENTER ORBIT COUNT"
  *Get starting orbit count
290 INPUT O1
  *Print instruction
300 PRINT "ENTER CURRENT YEAR"
  *Get current year
```

```
310 INPUT T1(0) . **T1(0) IS YEAR IN TIME ARRAY
320 PRINT "ENTER DISCHARGE MIN."
330 *Get discharge time
330 INPUT C3 **C3 IS LENGTH OF NIGHT
340 *print instruction
340 PRINT "ENTER CHARGE MIN."
340 *Get charge time
350 INPUT C1 **C1 IS LENGTH OF DAY
350 *Print instruction
360 PRINT "ENTER ORBITS TO SKIP"
360 *Get skip count
370 INPUT S1
370 *clear clock buffers and send clock hold pulse
400 CALL C(4,1,16,(2^15)) \ CALL C(4,1,16,0)
400 *Set up time input loop
410 FOR I=1 TO 9
410 *Set up to get digit
420 CALL C(4,1,16,(2^14)) \ CALL C(4,1,16,0)
420 *Get a time digit
430 CALL C(2,1,0,Z1%)
430 *Get another
440 NEXT I
440 *Reset counter and reset hold
450 CALL C(4,1,16,(2^15)) \ CALL C(4,1,16,(2^13)) \ CALL
450 C(4,1,16,0)
450 *Go to next program segment
500 CHAIN "MAINOP"
510 END
```

THIS STARTS THE MAIN OPERATING SECTION OF THE PROGRAM

```
2      REM "MAINOP" main operating program
      *Set up common variables
50     COMMON O1,C1,C3,T1(4),S1
      *Dimension arrays
500    DIM A1(6),A2(6),B1(6),B2(6),B3(6),B4(6),B5(6)
510    DIM B6(6),B7(6),B8(6),B9(6),C5(6),D2(6),D3(6)
520    DIM D6(13),D7(6),E1(6),E2(6),E3(6),E4(6),E5(6)
530    DIM E6(6),E7(6),E8(6),E9(6),F1(16),F2(16)
540    DIM T2(9),V3(7),V4(6),V5(13),V6(6),W1(6),W2(6)
550    DIM D9(6),A8(3),A9(3),A6(6),A7(6),A4(6)
555    DIM S4(6),S5(6),S6(6),S7(6)
560    DIM D1(6,23),D5(6,6),D8(6,23),T3(6,4),R9(5,9)
565    S6=48 \ FOR I=1 TO 6 \ S4(I)=S6 \ NEXT I
      *The next section initializes flags and summations
570    FOR I=1 TO 6 \ B3(I)=2 \ S5(I)=S4(I) \ NEXT I
575    FOR I=0 TO 5 \ FOR J=0 TO 9 \ R9(I,J)=0 \ NEXT J \ NEXT
I
580    L1=1.55 \ L2=1.55 \ L8=0 \ C$=":" \ C2=0 \ C4=0 \ P2=0 \
V1=0 \ V2=0
      *stop here to catch up ( type continue to resume)
590    STOP
      *Set crate no. and set to discharge phase
600    CALL CRATE(5) \ CALL C(5,0,16,2^2) \ CALL C(5,0,16,0)
      *Clear 1ppm log input
610    CALL C(4,1,16,(2^12)) \ CALL C(4,1,16,0)
      *Set up initial values
620    S2=0 \ M1=1 \ P8=0 \ P9=0 \ J9=0
630    R2=1.01 \ F3=0 \ K1=1/60
640    T8=0
      *Get input switch closures
1000   GOSUB 5000
      *check for shutdown
1010   IF F9=1 GOTO 1900
      *check power failure signal if zero skip to next check
1020   IF F1(0)=1 GOTO 1080
      *check power fail flag, if set go check signal again
1030   IF V1=1 GOTO 1900
      *power fail signal "on" flag not set so print out notice
header
1040   GOSUB 1810
      *print power fail message
1050   PRINT #2,"POWER FAILED SINCE"
      *print blanks, close output, & set power fail flag
1060   PRINT #2 \ CLOSE #2 \ V1=1
      *go beginning to check for power return
1070   GOTO 1000
      *if flag is zero continue normal input check
1080   IF V1=0 GOTO 1150
      *power was off, now on, get current time
1090   CALL C(4,1,16,(2^15)) \ CALL C(4,1,16,0) \ GOSUB 5200
```

```

*open output line & print header
1100 GOSUB 1810
    *print out message
1110 PRINT #2,"POWER RETURNED"
    *close output line & reset flag
1120 PRINT #2 \ CLOSE #2 \ V1=0
    *clear out 1ppm signal
1130 CALL C(4,1,16,(2^12)) \ CALL C(4,1,16,0)
    *go back to checking input signals
1140 GOTO 1000
    *if flag set go scan branch
1150 IF F2(10) = 1 GOTO 2000
    *set up battery loop to check print requests
1160 FOR I=1 TO 7
    *if recond sw set, set recond flag
1170 IF F2(I)=1 THEN V3(I)=1
    *if printed flag set skip printing
1180 IF P1=1 GOTO 1210
    *if print flag not set go check another
1190 IF F1(I)=0 GOTO 1210
    *if print requested set flag
1200 U1=1
    *get next
1210 NEXT I
    *if prints not requested skip
1220 IF U1=0 GOTO 1400
    *print header
1230 GOSUB 1810
    *set up battery loop
1240 FOR I=1 TO 6
    *skip if battery print not requested
1250 IF F1(I)=0 GOTO 1340
    *print battery values
1270 PRINT #2,"BATTERY=";I;"V=";D2(I);";I=";
    D3(I);";BPRC I=";D9(I);";SOC=";S5(I);";AHO=";(-1*A2(I))/60
    *set up to print cell voltages
1280 A=1 \ N=12 \ GOSUB 1850
    *print some more
1290 PRINT #2 \ A=13 \ N=23 \ GOSUB 1850
    *print temperatures
1300 PRINT #2 \ FOR I1=1 TO 6 \ PRINT #2,USING "
    #####.##",D5(I,I1) ; \ NEXT I1 \ PRINT #2
1310 FOR I=1 TO 12 \ PRINT #2, USING " #####.## ",D8(I,I1);
    \ NEXT I1 \ PRINT #2
1320 FOR I(1)=13 TO 23 \ PRINT #2,USING " #####.## ", D8(I,I1);
    \ NEXT I1
    *add spaces
1330 PRINT #2 \ PRINT #2
    *get another
1340 NEXT I
    *check bus data request
1350 IF F1(7)=0 GOTO 1380
    *print header
1360 PRINT #2,"BUS      VOLTS      CURR"

```

```

*print data
1370 FOR I=1 TO 3 \ PRINT #2,USING " #   ##.###   ##.###",
I,A9(I),A8(I) \ NEXT I
*close up print & set "printed" flag
1380 P1=1 \ CLOSE #2 \ U1=0
*if sw not set skip force night routine
1400 IF F1(14) = 0 GOTO 1430
*if already forced to night skip
1410 IF P3=1 GOTO 1430
*force night, set flag & clear begin flags
1420 CALL C(5,0,16,2^2) \ CALL C(5,0,16,0) \ PRINT "FORCE
NIGHT" \ P3=1 \ P4=0 \ V7=0 \ V8=0
*if sw not set skip force day routine
1430 IF F1(11)=0 GOTO 1460
*if already forced to day skip
1440 IF P4=1 GOTO 1460
*force day, set flags and clear begin flags
1450 CALL C(5,0,16,2^1) \ CALL C(5,0,16,0) \ PRINT "FORCE
DAY" \ P4=1 \ P3=0 \ V7=0 \ V8=0
*if sw not set skip begin night routine
1460 IF F1(12)=0 GOTO 1500
*if already begin night skip
1470 IF V7=1 GOTO 1500
*print message & set/reset flags
1480 PRINT "BEGIN NIGHT" \ V7=1 \ P3=0 \ P4=0 \ V8=0 \ C4=0
*go to 'end of orbit' routine
1490 GOTO 2530
*if sw not set, skip begin day routine
1500 IF F1(13)=0 GOTO 1540
*if already begin day skip
1510 IF V8=1 GOTO 1540
*set day output & set phase flag to change
1520 CALL C(5,0,16,2^1) \ CALL C(5,0,16,0) \ P2=1
*print message & set/reset flags
1530 PRINT "BEGIN DAY" \ V8=1 \ P3=0 \ P4=0 \ V7=0 \ C2=0
*test to see if tape on line
1540 IF F1(8)=1 GOTO 1570
*switch off was it on?
1550 IF M1=1 GOTO 1590
*was off return to beginning
1560 GOTO 1000
*tape off line sw. on, was it before?
1570 IF M1=1 GOTO 1000
*new off line request, close tape
1580 CLOSE #9 \ MI=1 \ GOTO 1000
*new on-line request, turn on tape output
1590 OPEN "MSO:DATA" FOR OUTPUT AS FILE #9, FILESIZE 1
*set flags and return
1600 M1=0 \ T9=0 \ GOTO 1000
*send out shutdown closure & set flag
1790 CALL C(5,0,16,(2^14)) \ F9=1
*send out alarm closure
1800 CALL C(5,0,16,(2^15)) \ CALL C(5,0,16,0)
*open printer file

```

```

1810 OPEN "LT:" FOR OUTPUT AS FILE #2
    *print header data
1820 PRINT #2,T1(0);C$;T1(1);C$;T1(2);C$;T1(3);C$;T1(4);
    "ORB=";O2;"P=";P5;"C2=";C8;"C4=";C9 \ RETURN
    *print cell data
1850 FOR I1=A TO N \ PRINT #2,USING " ##.#### ",D1(I,I1); \
NEXT I1 \ RETURN
    *send ippm pulse
1900 CALL C(3,0,16,3) \ CALL C(3,0,16,0)
    *return to beginning
1910 GOTO 1000

2000 REM SCAN BRANCH
    *send "latch" pulse to clock
2010 CALL C(4,1,16,(2^12+2^15)) \ CALL C(4,1,16,0)
    *send "scanning" pulses out
2020 CALL C(3,0,16,3) \ CALL C(3,0,16,0)
    *go scan all data & convert as necessary
2030 GOSUB 4000
    *go get "now" time
2040 GOSUB 5200
    *go check hi-lo limits
2050 GOSUB 7000
    *test for "initial" flag
2060 IF V2=1 GOTO 2090
    *store starting time
2070 FOR I=1 TO 6 \ FOR J=0 TO 4 \ T3(I,J)=T1(J) \ NEXT J \
NEXT I
    *set "initial" flag
2080 V2=1
    *set up loop
2090 FOR I=1 TO 6
    *check phase
2100 IF P2=1 GOTO 2130
    *check for first discharge phase scan if no skip
2110 IF C4>0 GOTO 2150
    *skip
2120 GOTO 2140
    *check for first phase scan if no skip
2130 IF C2>0 GOTO 2150
    *set up last scan value
2140 D7(I)=D3(I)
    *calculate current average
2150 N=(D3(I)+D7(I))/2
2152 IF D3(I)>0 GOTO 2154
2153 S5(I)=S5(I)+N*K1 \ GOTO 2155
2154 S5(I)=S5(I)+N*K1/R2
2155 IF F3=0 GOTO 2160
2156 IF P2=1 GOTO 2170
    *check for negative current
2160 IF D3(I)<0 GOTO 2180
    *calculate amps. in
2170 A1(I)=A1(I)+N \ W1(I)=W1(I)+(N*D2(I)) \ GOTO 2190

```

```

*calculate amps. out
2180 A2(I)=A2(I)+N \ W2(I)=W2(I)+(N*D2(I))
*update last current
2190 D7(I)=D3(I) \ (A3(I)=A3(I)+D9(I))
*temporarily store phase flag
2191 Y1=P2
*check trickle charge flag
2194 IF F8=0 GOTO 2200
*tickles charge on, reset SOC values
2196 S5(I)=S4(I) \ F7=1 \ T8=C2
*set trickle charge flag for output
2197 Y1=P2+10
2200 IF P2=0 GOTO 2230
*in charge find hi cells
2210 GOSUB 8350
*check if still in recond.
2230 IF V3(I)=1 GOTO 2670
*get another battery
2240 NEXT I
2245 IF F7=1 THEN F8=0
*check load bank total current
2250 A8(0)=A8(1)+A8(2)+A8(3) \ IF A8(0)<99 GOTO 2280
*out of limit go to shutdown
2260 GOSUB 1790
*print message
2270 PRINT #2,"TOTAL BUS I=";A8(0) \ CLOSE #2
*transmit data to smart system & mag tape
2280 GOSUB 5500
*set print parameters
2290 P5=P2 \ 02=01
*check phase
2300 IF P2=1 GOTO 2430
*update discharge counter & display
2310 C4=C4+1 \ PRINT "DISC MIN=";C4;"C3=";C3;"ORBIT NO.";
O1 \ C9=C4 \ C8=C2
2320 GOSUB 3000
*check for "Forced Day"
2330 IF P4=1 GOTO 2350
*go check power supply limits
2340 GOSUB 7600
*discharge time not up return to main
2350 IF C4<C3 GOTO 1000
*set up loop
2360 FOR I=1 TO 6
2362 S7(I)=S5(I)
*go check disch. hi-lo cells
2370 GOSUB 8200
*go get E-O-D H-L temps
2380 GOSUB 8500
*store results
2390 B9(I)=A \ B8(I)=L \ B7(I)=H
*next batt.
2400 NEXT I
*send out day pulse & set day flag * reset force & begin

```

```

flags
2410 CALL C(5,0,16,2^1) \ CALL C(5,0,16,0) \ P2=1 \ P4=0 \
V7=0 \V8=0
*return to main program
2420 GOTO 1000
*update charge counter
2430 C2=C2+1 \ PRINT "CHRG MIN=";C2;"C1=";C1;"ORBIT NO.";01
\ C8=C2
*go check power supply limits
2440 GOSUB 7800
*if charge time not up go to main
2450 IF C2<C1 GOTO 1000
*update orbit count
2460 O1=O1+1
*update orbit skip counter
2470 S2=S2+1
*check its value
2480 IF S2>0 THEN S2=-S1
*set up loop
2490 FOR I=1 TO 6
*go get END-O-PHASE temps
2496 S6(I)=S5(I)
2500 GOSUB 8500
*store results
2510 E9(I)=A \ E8(I)=L \ E7(I)=H
*go get next
2520 NEXT I
*send out night pulse & set day flags & reset force -
begin flags
2530 CALL C(5,0,16,2^2) \ CALL C(5,0,16,0) \ P2=0 \ P3=0 \
V7=0 \ V8=0
*set up loop
2540 OPEN "LS:" FOR OUTPUT AS FILE #1
*open line to printer
2550 FOR I=1 TO 6
*if in recon. skip printer
2560 IF V3(I)=1 GOTO 2590
*go print batt results
2570 G4=C4
*go print batt. orbital data
2580 GOSUB 6000
*next batt
2590 NEXT I
*close print
2595 T8=99
2600 CLOSE #1
*zero chrg-disch counters
2603 J9=J9+1
2604 IF J9>9 THEN J9=0
2610 C2=0 \ C4=0
*set up batt loop
2620 FOR I=1 TO 6
*test for recond. skip time if yes
2630 IF V3(I)=1 GOTO 2650

```

```

*load new sunset time
2640 FOR J=0 TO 4 \ T3(I,J)=T1(J) \ NEXT J
*next batt.
2650 NEXT I
*go to main
2660 GOTO 1000
*update discharge recond counter
2670 C5(I)=C5(I)+1
*check if recond still on
2680 IF F2(I)=0 GOTO 2770
*check if captest complete
2690 IF V4(I)=1 GOTO 2240
*check for end of captest
2700 IF D2(I)>26.45 GOTO 2240
*set captest complete flag
2710 V4(I) = 1
*set disch min, to captest time
2720 G4=C5(I)
*open output for captest info
2730 OPEN "LS:" FOR OUTPUT AS FILE #1
2735 GOSUB 8200
*go print orb (captest) info
2740 GOSUB 6000
*close output
2750 CLOSE #1
*return to next batt.
2760 GOTO 2240
*recond over clear flags & set up output
2770 V3(I)=0 \ V4(I)=0 \ G4=C5(I)
*clear disch (captest) counter
2780 C5(I) = 0
*go print summary data
2790 GOTO 2730
*subroutine to check bus current for day
3000 IF P9=0 GOTO 3060
*set up loop
3010 FOR I=1 TO 3
*check for good bus-current
3020 IF A8(I)>5 GOTO 3050
*bad limit go alarm
3030 GOSUB 1800
*print message
3040 PRINT #2, "BUS No.";I;"CURR=";A8(I) \ CLOSE #2
*get another
3050 NEXT I
*return
3060 RETURN
4000 REM SCAN DATA
*set up crate & clear begin/force flags
4010 CALL CRATE (4)
*set up battery loop
4020 FOR I=1 TO 6
*set up cell loop
4030 FOR J=1 TO 23

```

```

        *set up char. no.
4040 M% = 23*(I-1)+J+512 \ H=D1(I,J) \ U2=0
        *set up mux & adc at gain of 4 (+-2.56v)
4050 CALL C(1,0,16,M%)
        *set LAM status
4051 CALL C(1,0,27,,Q,X)
        *if not set try again
4052 IF Q=0 GOTO 4051
        *get adc results
4060 CALL C(1,1,0,Z1%)
        *convert to voltage
4070 D1(I,J)=(Z1%*78.125*10^(-6))
        *check for initial phase scan
4071 IF C4=0 GOTO 4080
4072 IF C2=0 GOTO 4080
4073 IF ABS(H-D1(I,J))<.01 GOTO 4080
        *check tries
4074 IF U2>2 GOTO 4080
        *incrmnt counter & go try again
4075 U2=U2+1 \ GOTO 4050
        *next cell
4080 NEXT J
        *next batt.
4090 NEXT I
        *set up batt. loop
4100 FOR I=1 TO 5
        *set up cell loop
4110 FOR J=1 TO 23
        *set up char no.
4120 M% = 652+23*(I-1)+J \ H=D8(I,J) \ U2=0
        *set up mux & adc (gain 1 +-2.56v)
4130 CALL C(1,0,16,M%)
        *check if conversion complete
4131 CALL C(1,0,27,,Q,X)
        *if not ready try again
4132 IF Q=0 GOTO 4131
        *get results
4140 CALL C(1,1,0,Z1%)
        *convert to voltage & pressure (30mv=150psig)
4150 D8(I,J)=(Z1%*78.125*10^(-5))*4.97
        *check jump in reading
4151 IF ABS(H-D8(I,J))<10 GOTO 4160
        *check if enough tries
4152 IF U2>2 GOTO 4160
        *not too many try again
4153 U2=U2+1 \ GOTO 4130
        *check for highest pressure
4160 IF A6(I)<D8(I,J) THEN A6(I)=D8(I,J) \ A7(I)=J
        *next cell
4170 NEXT J
        *next batt.
4180 NEXT I
        *change to crate 5
4190 CALL CRATE(5)

```

```

        *set up cell loop
4200 FOR J=1 TO 23
        *set up to check for bad readings
4210 H=D8(6,J) \ U2=0
        *set up mux & adc
4220 CALL C(8,0,16,(511+J))
        *check if conversion complete
4221 CALL C(8,0,27,,Q,X)
        *if not try again
4222 IF Q=0 GOTO 4221
        *get adc results
4230 CALL C(8,1,0,Z1%)
        *convert to volt & pressure
4240 D8(6,J)=(Z1%*78.125*10^(-5))*4.97
        *check jump in readings
4241 IF ABS(H-D8(6,J))<10 GOTO 4250
        *too many tries
4242 IF U2>2 GOTO 4250
        *go try again
4243 U2=U2+1 \ GOTO 4220
        *check for high pressure
4250 IF A6(6)<D8(6,J) THEN A6(6)=D8(6,J) \ A7(6) = J
        *next cell
4260 NEXT J
        *set up batt loop
4270 FOR I=1 TO 6
        *set up char no. & reset print flag
4280 M%=119+I \ H=D2(I) \ U2=0
        *set up mux & adc
4290 CALL C(8,0,16,M%)
        *check LAM
4291 CALL C(8,0,27,,Q,X)
4292 IF Q=0 GOTO 4291
        *get adc results
4300 CALL C(8,1,0,Z1%)
        *convert to volt
4310 D2(I)=(Z1%*6.26)/1000
        *check batt v jump
4311 IF ABS(H-D2(I))<.1 GOTO 4320
        *check tries
4312 IF U2>2 GOTO 4320
        *try again
4313 U2=U2+1 \ GOTO 4290
        *set up mux * adc
4320 CALL C(6,0,16,(I-1))
        *check LAM
4321 CALL C(6,0,27,,Q,X)
        *if not ready try again
4322 IF Q=0 GOTO 4321
        *get results
4330 CALL C(6,1,0,Z1%)
        *convert to volt & store it batt I
4340 D3(I)=Z1%*2.50000E-03
        *set up mux for BPRC current

```

```

4350 CALL C(6,0,16,(517+I))
    *check LAM
4351 CALL C(6,0,27,,Q,X)
    *if not ready try again
4352 IF Q=0 GOTO 4351
    *get results
4360 CALL C(6,1,0,Z1%)
    *convert and store BPRC current
4370 D9(I)=Z1%*6.25000E-04
    *next battery
4380 NEXT I
    *current correction factors
4390 D3(1)=D3(1)+0\D3(2)=D3(2)+0\D3(3)=D3(3)+0
4400 D3(4)=D3(4)-0\D3(5)=D3(5)+0\D3(6)=D3(6)+0
4410 D9(1)=D9(1)-2.00000E-03 \
    D9(2)=D9(2)-1.00000E-03 \
    D9(3)=D9(3)-8.00000E-03
4420 D9(4)=D9(4)-7.00000E-03 \
    D9(5)=D9(5)-6.00000E-03 \
    D9(6)=D9(6)-.011
    *set up batt loop
4430 FOR I=1 TO 6
    *set up meas. loop
4440 FOR J=1 TO 6
    *set up char no. & adc data
4450 M%=335+6*(I-1)+J
    *set up adc & mux
4460 CALL C(8,0,16,M%)
    *get results
4470 CALL C(8,1,0,Z1%)
    *convert to volts
4480 V=Z1%*.15625/1000
    *test for too high
4490 IF V>2.2303 THEN V=2.2303
    *test for too low
4500 IF V<-1.2575 THEN V=-1.2575
    *convert to res.
4510 R=((V+2.515)/(2.515-V))*3000
    *convert to deg C
4520 D5(I,J)=(5153.2/(LOG(R)+7.03721))-317.688
    *next meas
4530 NEXT J
    *next batt.
4540 NEXT I
4542 D5(2,3)=(D5(2,1)+D5(2,2)+D5(2,4)+D5(2,5)+D5(2,6))/5
    *set up loop for sas/ps.
4550 FOR I=1 TO 13
    *set up mux & adc data
4560 M%=578+I
    *set up mux & adc
4570 CALL C(8,0,16,M%)
    *check to see if conversion complete
4571 CALL C(8,0,27,,Q,X)
    *if not done try again
4572 IF Q=0 GOTO 4571
    *get results

```

```

4580 CALL C(8,1,0,Z1%)
  *convert to amps
4590 D6(I)=Z1%*78.125*10^(-3)
  *next sas
4600 NEXT I
  *set up loop for bus data
4610 FOR I=1 TO 3
  *adjust range and chan
4620 M%=575+I
  *set up mux
4630 CALL C(8,0,16,M%)
  *check to see if conversion complete
4631 CALL C(8,0,27,,Q,X)
  *if not done try again
4632 IF Q=0 GOTO 4631
  *get result
4640 CALL C(8,1,0,Z1%)
  *convert data
4650 A8(I)=(Z1%*78.125*10^(-5)*2)
  *adjust chan
4660 M%=125+I
  *set up mux
4670 CALL C(8,0,16,M%)
  *get results
4680 CALL C(8,1,0,Z1%)
  *convert to volts
4690 A9(I)=(Z1%*6.26)/1000
  *next bus
4700 NEXT I
  *reset print flag
4710 P1=0
4720 RETURN
5000 REM SUBROUTINE TO GET SWITCH CLOSURES
  *set up crate/get ok from module
5010 CALL CRATE(5)
  *get first set of inputs (iso-inputs)
5020 CALL C(2,0,0,Z1%)
  *get second set of inputs (non-iso)
5030 CALL C(2,1,0,Z2%)
  *convert both words to proper format
5040 Z1%=ABS(1+Z1%) \ Z2%=ABS(1+Z2%)
  *set up loop to check inputs
5050 FOR L=0 TO 15
  *set up compare valve & clear flags
5060 N=2^(15-L) \ F1(15-L)=0 \ F2(15-L)=0
  *compare a flag if no-go skip to next check
5070 IF Z1%-N<0 GOTO 5090
  *reduce input by compared valve & set flag
5080 Z1%=Z1%-N \ F1(15-L)=1
  *compare a flag if no-go skip to next check
5090 IF Z2%-N<0 GOTO 5110
  *reduce input by compared valve & set flag
5100 Z2%=Z2%-N \ F2(15-L)=1
  *get next get to compare

```

```

5110 NEXT L
    *return to main program
5120 IF F2(7)=0 GOTO 5150
5130 IF F7=1 GOTO 5160
5140 F8=1 \ GOTO 5160
5150 F7=0
5160 RETURN
5200 REM GETIME
    *set up crate & set hold/reset
5210 CALL CRATE(5)
    *set up loop
5220 FOR I=1 TO 9
    *advance char. counter in clock
5230 CALL C(4,1,16,(2^14)) \ CALL C(4,1,16,0)
    *get inputs
5240 CALL C(2,1,0,Z1%)
    *adjust results
5250 N1(I)=ABS(1+Z1%)
    *next input
5260 NEXT I
    *reset counter \ and release hold
5270 CALL C(4,1,16,(2^15)) \ CALL C(4,1,16,(2^13)) \ CALL C(
    4,1,16,0)
    *set up decode loop
5280 FOR I=1 TO 9
    *clear clock char
5290 T2(I)=0
    *set up bit loop
5300 FOR J=0 TO 3
    *set up compare no.
5310 N=2^(14-J)
    *compare bits if yes continue
5320 IF N1(I)-N<0 GOTO 5350
    *adjust value
5330 N1(I)=N1(I)-N
    *add bit to char word
5340 T2(I)=T2(I)+2^(3-J)
    *next bit
5350 NEXT J
    *next char
5360 NEXT I
    *build days
5370 T1(1)=100*T2(1)+10*T2(2)+T2(3)
    *build hours
5380 T1(2)=10*T2(4)+T2(5)
    *build minutes
5390 T1(3)=10*T2(6)+T2(7)
    *build seconds
5400 T1(4)=10*T2(8)+T2(9)
    *return
5410 RETURN
5500 REM SUBROUTINE TO TRANSMIT DATA TO "SMART" SYSTEM
    *open file #3 (rs232 output to "smart" system)
5510 OPEN "TV:" FOR OUTPUT AS FILE #3

```

```

*ttransmit start char
5520 PRINT #3,"A"
*set loop and transmit time
5530 FOR I=0 TO 4 \ PRINT #3,T1(I) \ NEXT I
*ttransmit header data
*output orbit count, phase, and charge counters
5540 PRINT #3,01 \ PRINT #3,Y1 \ PRINT #3,C2 \ PRINT #3,C4
*set up batt loop
5550 FOR I=1 TO 6
*output batt. no.
5560 PRINT #3,I
*output cell volt.
5570 FOR J=1 TO 23 \ PRINT #3,D1(I,J) \ NEXT J
*output cell press
5580 FOR J1=1 TO 23 \ PRINT #3,D8(I,J1) \ NEXT J1
*output bat v & bat I
5590 PRINT #3,D2(I) \ PRINT #3,D3(I) \ PRINT #3,D9(I)
*output temps
5600 FOR J=1 TO 6 \ PRINT #3,D5(I,J) \ NEXT J
*output recond flags
5610 PRINT #3,V3(I)
*get another
5620 NEXT I
*output sas currents
5630 FOR I=1 TO 13 \ PRINT #3,D6(I) \ NEXT I
*output bus data
5640 FOR J=1 TO 3 \ PRINT #3,A8(J) \ PRINT #3,A9(J) \ NEXT J
*close file
5650 CLOSE #3
*check for mag tape record
5660 IF M1=1 GOTO 5880
*check skip orbit
5670 IF S2<0 GOTO 5880
*check skip scan
5680 IF F1(9)=0 THEN S3=0 \ GOTO 5710
*check for skip
5690 IF S3=0 GOTO 5710
*reset skip flag
5700 S3=-1 \ GOTO 5870
*increment record counter
5710 T9=T9+1
*check for too many records
5720 IF T9<3700 GOTO 5740
*too many print message
5730 PRINT "OUT OF TAPE" \ GOTO 5880
*print start char
5740 PRINT #9,"A"
*record time
5750 FOR I=0 TO 4 \ PRINT #9,T1(I) \ NEXT I
*record header data
5760 PRINT #9,01 \ PRINT #9,P2 \ PRINT #9,C2 \ PRINT #9,C4
*set up for battery loop
5770 FOR I=1 TO 6
*record batt no.

```

```

5780 PRINT #9,I
    *set up loop and record cell volt
5790 FOR J=1 TO 23 \ PRINT #9,D1(I,J) \ NEXT J
    *set up loop and record cell press
5800 FOR J1=1 TO 23 \ PRINT #9,D8(I,J1) \ NEXT J1
    *record batt data
5810 PRINT #9,D2(I) \ PRINT #9,D3(I) \ PRINT #9,D9(I)
    *record batt temps
5820 FOR J=1 TO 6 \ PRINT #9,D5(I,J) \ NEXT J
    *record recond. flag
5830 PRINT #9,V3(I)
    *get another batt
5840 NEXT I
    *set up loop to record sas data
5850 FOR I=1 TO 13 \ PRINT #9,D6(I) \ NEXT I
    *set up loop for bus data
5860 FOR J=1 TO 3 \ PRINT #9,A8(J) \ PRINT #9,A9(J) \ NEXT J
    *add to skip counter
5870 S3=S3+1
    *return
5880 RETURN
6000 REM ORBDAT SUBROUTINE TO PRINT OUT ORBIT DATA
    *print first part of 1st line
6010 PRINT #1,"BAT ORBIT      SUNSET TIME      BAT WHO
        BAT EFF DCH CHG RR ";
    *print secon part of 1st line
6020 PRINT #1,"      DOD      AHO      BPRC AH      CHI T-CAV T-CLO T--
        DHI T-DAV T-DLO T"
    *print first part of 1st data line
6030 PRINT #1,USING " # ##### ####:###:###:###",I,01-1,
        T3(I,0),T3(I,1),T3(I,2),T3(I,3),T3(I,4);
    *check for zeros & set to limit valves
6040 IF A1(I)=0 THEN A1(I)=10000
6050 IF A2(I)=0 THEN A2(I)=1
6060 IF W1(I)=0 THEN W1(I)=1
6070 IF W2(I)=0 THEN W2(I)=1
    *calculate data
6080 G1=-1*W2(I)/60 \ G2=-1*W2(I)/W1(I) \ G3=A1(I)/(-1*A2(I))
6082 IF F3=0 THEN A4(I)=0
6084 G5=(-1*A2(I)/33)+A4(I)
6086 A4(I)=G5-(A1(I)/(R2*33)) \ G8=A4(I)
    *calculate data
6090 G6=-1*A2(I)/60 \ G7=A3(I)/60
6092 R9(I-1,J9)=G3 \ V=0
6094 FOR I=0 TO 9 \ V=V+R9(I-1,I2) \ NEXT I2 \ R=V/10
    *print data
6100 PRINT #1 USING " #####.#      .#####",G1,G2; \ PRINT #1,
        TAB(49),G4;TAB(54);C2;" ";
    *print data
6110 PRINT #1,USING "##.### ##.## ##.## ##.##",G3,G5,G6
        ,G7;
    *print data
6120 PRINT #1,USING " ##.## ##.## ##.## ##.## ##.## ##.## ##.##"
        ,E7(I),E9(I),E8(I),B7(I),B9(I),B8(I)

```

```

*print first part of second header
6130 PRINT #1,"DHI CV--CNO--AV CV--DLO CV--CNO";
*print 2nd part of 2nd header
6140 PRINT #1,TAB(40); "CHI CV--CNO--AV CV--CLO CV--CNO";
\ B5=B6(I)/23 \ E5=E6(I)/23
6150 PRINT #1,TAB(80); "HI PRESS--CNO      DODD    SOC    SOD
TTT RRAV:
*print the data
6061 PRINT #1, USING " .###   ##  .###  .###  ##",B1(I),
B2(I),B5,B3(I),B4(I);
6170 PRINT #1,TAB(40); \ PRINT #1,USING " .###   ##  .###
#.### ##",E1(I),E2(I),E5,E3(I),E4(I);
6180 PRINT #1,TAB(80); \PRINT #1,USING "##.#   ##  ##.#
# ##.## ##.## ##.##",A6(I),A7(I),A4(I),S6(I),S7(I),
T8,R
*print space
6190 PRINT #1
*skip if batt in recond
6200 IF V3(I)=1 GOTO 6230
*clear sums
6205 FOR J=1 TO 6 \ S4(J)=S6 \ NEXT J
6210 A1(I)=0 \ A2(I)=0 \ W1(I)=0 \ W2(I)=0 \ A3(I)=0
6220 E1(I)=0 \ B3(I)=2 \ A6(I)=0
*return
6230 RETURN
7000 REM ROUTINE TO CHECK HI-LO LIMITS
*set limit value
7010 L9=L1
*set up batt loop
7020 FOR I=1 TO 6
*check for limit
7030 IF I>3 THEN L9=L2
*set up cell loop
7040 FOR I1=1 TO 23
*check limit, if out go shutdown
7050 IF D1(I,I1)>L9 GOTO 7140
*check lo limit
7060 IF D1(I,I1)<L8 GOTO 7140
*next cell
7070 NEXT I1
*check batt curr
7080 IF D3(I)<-30 GOTO 7120
*check batt curr hi
7090 IF D3(I)>25 GOTO 7120
*get another batt
7100 NEXT I
*return
7110 RETURN
*go shutdown
7120 GOSUB 1790
*print message
7130 PRINT #2,"BATTERY NO.";I;"CURRENT=";D3(I) \ CLOSE #2 \
GOTO 7100
*go shutdown

```

```

7140 GOSUB 1790
    *print message
7150 PRINT #2,"BATT=";I;"CELL=";I1;"V=";D1(I,I1) \ CLOSE #2 \
    GOTO 7070
7600 FOR I=1 TO 13
7610 U2=0
    *check limit
7620 IF D6(I)<5 THEN V5(I)=0 \ GOTO 7700
    *check if new out of limit
7630 IF V5(I)=1 GOTO 7700
7640 CALL CRATE(5) \ IF U2>2 GOTO 7680
7650 CALL C(8,0,16,(578+I))
    *check LAM
7651 CALL C(8,0,27,,Q,X)
    *if not ready try again
7652 IF Q=0 GOTO 7651
7660 CALL C(8,1,0,Z1%) \ D6(I)=Z1%*78.125 * 10^(-3)
7670 U2=U2+1 \ GOTO 7620
    *go alarm
7680 GOSUB 1800
    *print message
7690 PRINT #2,"SUPPLY NO.";I;"CURR=";D6(I) \ CLOSE #2 \
    V5(I) =1
    *get another
7700 NEXT I
7710 RETURN
    *special night routine
    *check flag
7800 IF P8=0 GOTO 7870
    *over 5 min. into phase
7810 IF C2>5 GOTO 7870
    *set up loop
7820 FOR I=1 TO 13
    *check limit
7830 IF D6(I)>5 GOTO 7860
    *out of limit go alarm
7840 GOSUB 1800
    *print message
7850 PRINT #2,"SUP #";I;"I=";D6(I) \ CLOSE #2
    *get another
7860 NEXT I
    *return
7870 RETURN
8200 REM SUBROUTINE TO GET HI-LO CELLS DURING DISCHARGE
    *set flag
8210 U=0
    *set up loop
8220 FOR J=1 TO 23
    *compare if lower skip to replace
8230 IF B3(I)<=D1(I,J) GOTO 8250
    *replace with new valve & set replace cell no. and set
    new hi
8240 B3(I)=D1(I,J) \ B6(I)=0 \ B4(I)=J \ U=1
    *if higher get next

```

```

8250 NEXT J
    *check flag if 0 skip
8260 IF U=0 GOTO 8320
    *set limit
8270 B1(I)=0
    *set loop
8280 FOR J1=1 TO 23
    *if less than high skip
8290 B6(I)=B6(I)+D1(I,J) \ IF B1(I)>D1(I,J1) GOTO 8310
    *replace high
8300 B1(I)=D1(I,J1) \ B2(I)=J1
    *get another
8310 NEXT J1
8320 RETURN
8350 REM SUBROUTINE TO GET HI-LO CELLS DURING CHARGE
8360 U=0
    *set up loop
8370 FOR J=1 TO 23
    *reset "try" counter
8380 U2=0
    *check for higher cell if yes skip to replace
8390 IF E1(I)>=D1(I,J) GOTO 8410
    *replace hi cell and batt v & get cell no. v
8400 E1(I)=D1(I,J) \ E6(I)=0 \ E2(I)=J \ U=1
    *get another
8410 NEXT J
8420 IF U=0 GOTO 8480
    *set lo cell
8430 E3(I)=2
    *set up loop
8440 FOR J1=1 TO 23
    *compare for lows
8450 E6(I)=E6(I)+D1(I,J1) \ IF E3(I)<D1(I,J1) GOTO 8470
    *replace values
8460 E3(I)=D1(I,J1) \ E4(I)=J1
    *get another
8470 NEXT J1
8480 RETURN
8500 REM SUBROUTINE TO GET HI-LO TEMPS
    *set up limit
8510 H=-15 \ L=25 \ N=0
    *set up loop
8520 FOR J=1 TO 6
    *get sums
8530 N=N+D5(I,J)
    *check for new lo
8540 IF L>D5(I,J) THEN L=D5(I,J)
    *check for new hi
8550 IF H<D5(I,J) THEN H=D5(I,J)
    *get another
8560 NEXT J
    *compute average
8570 A=N/6
    *check for out of limit average

```

```
8580 IF A>25 GOTO 8610
    *check for lo out of limit
8590 IF A<-5 GOTO 8610
8600 RETURN
    *chamber shutdown and alarm
8610 CALL C(5,0,16,(2^13)) \ GOSUB 1790
    *print message
8620 PRINT #2,"BATTERY";I;"TEMP=";A \ CLOSE #2 \ GOTO 8600
9999 END
```



## APPENDIX E

NAME	ST6BINT
SECTION	ST6B2
LIST	DBG

```
;*****  
;*****  
;*****  
;***** SPACE TELESCOPE *****  
;***** SIX BATTERY TEST *****  
;***** INTERRUPT HANDLER ROUTINE *****  
;*****  
;***** BY: JOHN R. BUSH, JR. *****  
;*****  
;***** LATEST VERSION: 02/09/88 *****  
;*****  
;*****  
CR EQU ODH  
LF EQU OAH  
CU EQU 15H  
EOT EQU 04H  
SP EQU 20H  
TTYBASE EQU 00COH  
;  
GLOBAL TTYINT, TTYSETUP, WP2
```

```

;
;INTERRUPT ENTRY POINT
;
TTYINT    TB      21          ;IF SET, RECEIVED A CHAR
        JEQ     RCHAND      ;GO TO RECEIVER HANDLER
TXHAND    MOVB   @TXBUFF(R4),RO ;GET NEXT CHAR TO XMIT
        SRL     RO,8
        CI      RO,EOT
        JEQ     LASTCHAR    ;IS IT THE END?
        CI      RO,3CH      ;YES, JUMP
                ;< INDICATES MORE DATA
                ;ON "D" COMMAND
        JEQ     MORED       ;NO POINT TO NEXT CHAR
        INC     R4
        BL      @TXCHAR     ;TRANSMIT RO
RTWP      RTWP
LASTCHAR  CLR    RO          ;THROUGH THIS TIME
        CLR    R4          ;NULL
        BL      @TXCHAR     ;TO CLEAR INTERRUPT
        SBZ    19          ;DISABLE 9902 INTERRUPT
        RTWP
TXCHAR    SBO   16          ;TURN ON XMITTER
TXRDY    TB      22          ;SEE IF XMITTER READY
        JNE     TXRDY
        SLA    RO,8
LDCR      LDCR   RO,8
        SBZ    16          ;SHIFT FOR LDCR
        B      *R11         ;SEND CHAR
                ;TURN OFF XMITTER
                ;RETURN
;
MORED     B      MOREDISP   ;GET IN RANGE
;
;
;
;CONVERT RO TO ASCII
;
TASCII    AI      RO,30H     ;FOR ALL ASCII
        CI      RO,3AH     ;A - F?
        JLT    NOCONV    ;NO, OK
        AI      RO,7
NOCONV   B      *R11        ;FOR LETTERS
;
;
```

```

; IF JUST RECEIVED A CHAR YOU ARE HERE
;
RCHAND STCR R0,8 ; GET IT
        SRL R0,8 ; SHIFT TO LSB
        SBO 18 ; RESET INTERRUPT
        ANDI R0,007FH ; STRIP PARITY
        CI RO,CU ; IS IT A CONTROL U?
        JEQ CUTASK ; GO DO IT
        CI RO,CR ; IS IT A CR?
        JEQ CRTASK ; GO DO IT
        BL @TXCHAR ; ELSE, ECHO CHARACTER
                      ; TXCHAR ALSO SHIFTS SO
                      ; DONT NEED
;
;SLA      R0,8 ; NEXT STEP HERE.....
;
MOVVB    R0,@RCBUFF(R3) ; SHIFT FOR BYTE STORE
INC      R3 ; (HERE AND ELSEWHERE)
RTWP
;
; CONTROL U TASK
;
CUTASK CLR R3
        CLR R4
        MOVVB @CUMSG(R4),@TXBUFF(R4)
        INC R4
        MOVVB @CUMSG(R4),@TXBUFF(R4)
        INC R4
        BL @PROMPT
        RTWP
;
; CR TASK ... HERE GOES
;
CRTASK SLA R0,8
        MOVVB R0,@RCBUFF(R3) ; STORE CR
FDGS CLR R3
        CLR R4
        MOVVB @RCBUFF (R3),R0
        INC R3
        SRL R0,8
        CI RO,"X" ; X?
        JEQ XTASK
        CI RO,"S" ; S?
        JEQ STASK
        CI RO,"D" ; D?
        JEQ DTASK
        BL @QTASK ; NONE ON THE ABOVE,
                      ; ABORT
        RTWP

```

```

; X COMMAND ROUTINE
;
XTASK    LI      R1,XTABE      ; X TABLE END ADDRESS
         LI      R2,XTAB       ; X TABLE START ADDRESS
         BL      @LDPAR        ; GET PARAMETER ADDRESS
         MOV    RO,RO          ; CHECK FOR ERROR
         JEQ    PQTASK        ; NOT SUCCESSFUL, ABORT
         MOV    *RO,R1          ; GET DATA
         MOV    R1,RO          ; COPY TO RO
         BL     @NEWLINE       ; PUT CR,LF INTO TXBUFF
         BL     @CONTBUFF      ; CONVERT TO ASCII, THEN
                               ; TO TXBUFF
         BL     @PROMPT        ; ADD A PROMPT
         RTWP
;

; S TASK COMMAND ROUTINE
;
STASK    LI      R1,STABE      ; S TABLE END ADDRESS
         LI      R2,STAB        ; S TABLE START ADDRESS
         LI      R6,5           ; ABORT POSITION FOR CR
                               ; AT WRONG PLACE
         BL      @LDPAR        ; GET PARAMETER ADDRESS
         MOV    RO,RO          ; SEE IF CLEAR
         JEQ    PQTASK        ; UNSUCCESSFUL, ABORT
         BL     @CKDEL         ; GOOD DELIMITER?
         MOV    R1,R1          ; SEE IF CLEAR
         JEQ    PQTASK        ; NO, ABORT
         BL     @GDATAAD       ; TO GET DATA FROM
                               ; RCBUFF
         MOV    R1,R1          ; SEE IF CLEAR
         JEQ    PQTASK        ; YES, NOT SUCCESSFUL,
                               ; ABORT
         MOV    R2,*RO          ; STORE NEW DATA,
         CLR    R4             ; AND
         BL     @PROMPT        ; GET
         RTWP
;
```

```

;
; D TASK COMMAND ROUTINE
;

DTASK    LI      R6,2          ; ABORT POSITION FOR CR
         CLR    R7
         CLR    R8
         BL     @GDATAAD   ; GET START ADDR
         MOV    R1,R1       ; SEE IF CLEAR
         JEQ    PQTASK    ; YES, ABORT
         LI     R7,1        ; MAKE START ADDRESS TO
         SZC   R7,R2       ; BE THE NEXT LOWEST
                           ; ADDRESS
         MOV    R2,R7       ; IF IT WAS ODD. SAVE IN
                           ; R7.
         CI    R9,OODOH    ; WAS LAST CHAR A CR?
         JNE    COND      ; NO
SDADD    BL     @NEWLINE   ; START A NEWLINE
         MOV    R7,RO       ; PUT ASCII IN TXBUFF
         BL     @CONTBUFF  ; ADD A SPACE
         BL     @ADSPCE    ; GET DATA
         MOV    *R7,RO      ; TO TXBUFF
         BL     @CONTBUFF  ; ADD A PROMPT
         BL     @PROMPT    ; GET OUT
         RTWP

;
; CHECK FOR SECOND ADDRESS
;

COND    BL     @GDATAAD   ; GET END ADDRESS
         MOV    R1,R1       ; SEE IF CLEAR
         JEQ    PQTASK    ; ABORT
         LI     R8,1        ; MAKE END ADDRESS TO BE
                           ; NEXT
         SZC   R8,R2       ; LOWEST ADDRESS IF IT
                           ; WAS ODD.
         MOV    R2,R8       ; SAVE END ADDRESS
         MOV    R7,R2       ; START ADDR
         C     R2,R8       ; MAKE SURE END IS >
                           ; THAN START
         JHE    SDADD    ; IT WAS NOT, SO JUST DO
                           ; ONE

```

```

;
; IF HERE, START LOADING TXBUFF ONE LINE AT A TIME, ENDING
; THE LINE ON XXXEH WITH THE LAST CHARACTER BEING A "<" (3CH)
; IF DTASK IS NOT FINISHED. START NEW LINES ON XXXOH.
; WHEN LAST DATA IS LOADED, DO "BL @PROMPT".
;

MOREDISP BL      @NEWLINE          ; START A NEW LINE
        MOV     R7,RO
        BL     @CONTBUFF        ; LOAD ADDR IN TXBUFF
MOREDL  BL      @ADSPCE           ; ADD A SPACE
        MOV     *R7,RO          ; LOAD DATA
        BL     @CONTBUFF        ; DATA TO TXBUFF
        C      R7,R8            ; CHECK FOR END
        JHE    DEND
        MOV     R7,RO
        ANDI   RO,OFH           ; STRIP ALL BUT LSN
        CI     RO,OEH           ; IS IT AN E?
        JEQ    ADLA             ; YES, ADD LEFT ARROW
        INCT   R7               ; ELSE, INC TO NEXT
                                ; ADDRESS
        JMP    MOREDL           ; AND DO AGAIN
ADLA    LI     RO,3COOH
        MOVB  RO,@TxBuff(R4)
        INCT   R7
        CLR    R4
        SBO    19                ;ENABLE 9902 INTERRUPT
        RTWP
DEND    BL      @PROMPT
        RTWP

```

```

;
; SUBROUTINE TO LOAD A PARAMETER FROM RCBUFF
; SEARCH TABLE STARTING AT R2, ENDING AT
; R1 AND RETURN ADDRESS OF PARAMETER IN R0.
; IF INPUT WAS JUST XC, WILL SUBSTITUTE D8040,805E
; IN ORDER TO DISPLAY ALL ANALOG INPUT CHANNELS.
; IF UNSUCCESSFUL, RETURNS OS IN R0.
;
LDPAR    CLR      R0
         CLR      R5
         MOVB   @RCBUFF(R3),R0 ; FIRST CHAR
         INC     R3
         MOVB   @RCBUFF(R3),R5 ; SECOND CHAR
         INC     R3
         SRL    R5,8
         A      R5,R0          ; R0 HAS PARAMETER
         CI     RO,430DH        ; WAS IT JUST XC?
         JEQ    DCS
         FPARL  C      RO,*R2+ ; MATCH?
         FPARL  JEQ    FPAR      ; YES
         INCT   R2      ; NO, SKIP OVER ADDRESS
         C      R2,R1          ; END OF TABLE?
         JHE    NPAR      ; YES, NO MATCH
         JMP    FPARL     ; NO MATCH YET, TRY AGAIN
;
FPAR     MOV     *R2,R0          ; LOAD ADDRESS OF PARAMETER
         B      *R11
;
NPAR     CLR      R0          ; NO MATCH, RETURN ZERO
         B      *R11
;
DCS      CLR      R3
DCSL    MOVB   @DDCS(R3),@RCBUFF(R3)
         MOVB   @DDCS(R3),R0
         INC     R3
         SRL    R0,8
         CI     RO,CR
         JNE    DCSL
         B      FDCCS
;
; SUBROUTINE TO CHECK NEXT RCBUFF CHAR FOR A VALID
; DELIMITER (BLANK OR COMMA), RETURNS ZERO IN R1 IF
; NOT SUCCESSFUL.
;
CKDEL    CLR      R1
         MOVB   @RCBUFF(R3),R1
         INC     R3
         CI     R1,2000H        ; SPACE?
         JEQ    GDDEL     ; YES
         CI     R1,2COOH        ; COMMA?
         JEQ    GDDEL     ; YES
         CLR      R1          ; NOT SUCCESSFUL
         B      *R11          ; BRANCH OUT

```

```

;
; SUBROUTINE TO GET DATA FROM RCBUFF, R3 IS OFFSET,
; SEARCH RCTABLE UNTIL FIND GOOD DELIMITER OR CR,
; ROTATING GOOD DATA INTO R2; IF FIND BAD ASCII CHAR,
; RETURN ZEROS IN R1. DO NOT USE R0 !!
;

GDATAAD MOV      R11,R10          ; NESTED SUBROUTINE
;                                LINKAGE
;
;                                CLR      R2
;                                CLR      R1
;                                MOVB    @RCBUFF(R3),R1
;                                INC     R3
;                                MOV     R1,R9           ; SAVE FOR DTASK
;                                CI      R1,2000H        ; SPACE?
;                                JEQ    FDELCR          ; YES
;                                CI      R1,2COOH        ; COMMA?
;                                JEQ    FDELCR          ; YES
;                                CI      R1,ODOOH        ; CR?
;                                JEQ    FDELCR          ; YES
;                                BL      @FRASCI          ; NO, TEN WHAT IS IT?
;                                MOV     R5,R5           ; GOOD DATA?
;                                JEQ    BDDATA          ; NO, GET OUT
;                                SLA    R2,4            ; YES
;                                A      R1,R2           ; ADD INTO R2
;                                JMP    GDTL            ; AND DO UNTIL DELIMITER
;                                OR CR
;
FDELCR   C      R3,R6          ; IF THIS HAPPENS AT
;                                CHAR + R6
;                                JEQ    BDDATA          ; THEN NOTHING WAS
;                                ; THERE, ABORT.
;
;                                SETO   R1
;                                B      *R10           ; SIGNAL GOOD DATA
;
BDDATA   CLR   R1
;                                B      *R10           ; SIGNAL BAD DATA
;
FRASCI  SRL   R1,8            ; CONVERT FROM ASCII
;                                AI      RI,-30H        ; SUBTRACT 30H
;                                JLT    NOTAC           ; IF LESS THAN ZERO,
;                                ; ABORT
;
;                                CI      R1,10           ; SEE IF FINISHED
;                                JLT    GDAC             ; YES
;                                AI      R1,-7            ; FOR LETTERS
;                                JLT    NOTAC           ; ABORT
;                                CI      R1,OFH           ; BIGGER THAN F?
;                                JGT    NOTAC           ; YES, YOU GUessed IT
;                                ; -- ABORT
;
GDAC    SETO  R5
;                                B      *R11           ; SIGNAL GOOD DATA
;
NOTAC   CLR   R5
;                                B      *R11

```

```

;
; SUBROUTINE TO CONVERT RO TO ASCII AND STORE
; IN TXBUFF. DESTROYS RO
;
CONTBUFF MOV      R11,R10          ; FOR NESTED SUBROUTINE
                                ; LINKAGE
        MOV      RO,R1           ; COPY DATA
        SRL      RO,12           ; SHIFT TO FIRST CHAR
        BL       @BUFFSUB        ; CONVERT AND STORE
        SRL      RO,8            ;
        BL       @BUFFSUB
        SRL      RO,4            ;
        BL       @BUFFSUB
        BL       @BUFFSUB
        B       *R10
BUFFSUB  MOV      R11,R9          ; FOR NESTED LINKAGE
        ANDI    RO,OFH           ; STRIP ALL BUT LSN
        BL       @TASCII          ; TO ASCII
        SLA     RO,8            ;
        MOVB   RO,@TXBUFF(R4)
        INC    R4
        MOV    R1,RO
        B     *R9
;
; SUBROUTINE TO PUT CR,LF INTO TXBUFF
;
NEWLINE  LI      R1,ODOOH
        CLR    R4
        MOVB  R1,@TXBUFF(R4)
        INC    R4
        LI      R1,OAOOH
        MOVB  R1,@TXBUFF(R4)
        INC    R4
        B     *R11
;
; SUBROUTINE TO ADD SPACE TO TXBUFF
;
ADSPCE   LI      R1,2000H
        MOVB  R1,@TXBUFF(R4)
        INC    R4
        B     *R11

```

```
;  
; Q TASK  
;  
QTASK    CLR      R4  
QTLPI    MOVB    @QMSG(R4),@TXBUFF(R4)  
          MOVB    @TXBUFF(R4),R0  
          SRL     R0,8  
          INC     R4  
          CI      R0,"?"  
          JNE     QTLPI  
PROMPT   CLR      R3  
PRLPI    MOVB    @PMSG(R3),@TXBUFF(R4)      ;MOVE CHAR  
          MOVB    @TXBUFF(R4),R0      ; CHECK FOR EOT  
          SRL     R0,8  
          INC     R3  
          INC     R4  
          CI      R0,EOT  
          JNE     PRLPI  
          CLR      R3  
          CLR      R4  
          SBO    19      ; ENABLE 9902 INTERRUPT  
          B       *R11
```

```

;
; TABLE OF X PARAMETERS
;
XTAB    ASCII    "C0"
WORD    8040H
ASCII    "C1"
WORD    8042H
ASCII    "C2"
WORD    8044H
ASCII    "C3"
WORD    8046H
ASCII    "C4"
WORD    8048H
ASCII    "C5"
WORD    804AH
ASCII    "C6"
WORD    804CH
ASCII    "C7"
WORD    804EH
ASCII    "C8"
WORD    8050H
ASCII    "C9"
WORD    8052H
ASCII    "CA"
WORD    8054H
ASCII    "CB"
WORD    8056H
ASCII    "CC"
WORD    8058H
ASCII    "CD"
WORD    805AH
ASCII    "CE"
WORD    805CH
ASCII    "CF"
WORD    805EH
ASCII    "DE"
WORD    8092H
ASCII    "TD"
WORD    8094H
ASCII    "R1"
WORD    8060H
ASCII    "R2"
WORD    8062H
ASCII    "R3"
WORD    8064H
ASCII    "A1"
WORD    8066H
ASCII    "A2"
WORD    8068H
ASCII    "A3"
WORD    806AH
ASCII    "HI"
WORD    806CH

```

ASCII	"LI"
WORD	806EH
ASCII	"H2"
WORD	8070H
ASCII	"L2"
WORD	8072H
ASCII	"H3"
WORD	8074H
ASCII	"L3"
WORD	8076H
ASCII	"H4"
WORD	8078H
ASCII	"L4"
WORD	807AH
ASCII	"H5"
WORD	807CH
ASCII	"L5"
WORD	807EH
ASCII	"H6"
WORD	8080H
ASCII	"L6"
WORD	8082H
ASCII	"UH"
WORD	8084H
ASCII	"UL"
WORD	8086H
ASCII	"LH"
WORD	8088H
ASCII	"LL"
WORD	808AH
ASCII	"PI"
WORD	808CH
ASCII	"P2"
WORD	808EH
ASCII	"P3"
WORD	8090H
ASCII	"M1"
WORD	8096H
ASCII	"M2"
WORD	8098H
ASCII	"M3"
WORD	809AH
ASCII	"I1"
WORD	809CH
ASCII	"I2"
WORD	809EH
ASCII	"I3"
WORD	80A0H
ASCII	"PS"
WORD	80A4H
ASCII	"ES"
WORD	80A6H
ASCII	"TR"

WORD	8048H
ASCII	"NS"
WORD	80AAH
ASCII	"KI"
WORD	80B0H
ASCII	"PO"
WORD	80A2H
ASCII	"CT"
WORD	80B2H
ASCII	"SO"
WORD	80BAH
ASCII	"TS"
WORD	80BCH
ASCII	"PL"
WORD	80BEH
ASCII	"ET"
WORD	80C4H
ASCII	"NR"
WORD	80CAH
ASCII	"PR"
WORD	80CCH
ASCII	"EP"
WORD	80D4H
ASCII	"D1"
WORD	80D6H
ASCII	"D2"
WORD	80D8H
ASCII	"D3"
WORD	80DAH
ASCII	"D4"
WORD	80DCH
ASCII	"D5"
WORD	80DEH
ASCII	"D6"
WORD	80EOH
XTABE	EQU \$

TABLE OF S PARAMETERS

STAB	ASCII	"DE"
	WORD	8092H
	ASCII	"TD"
	WORD	8094H
	ASCII	"A1"
	WORD	8066H
	ASCII	"A2"
	WORD	8068H
	ASCII	"A3"
	WORD	806AH
	ASCII	"HI"
	WORD	806CH
	ASCII	"L1"
	WORD	806EH
	ASCII	"H2"
	WORD	8070H
	ASCII	"L2"
	WORD	8072H
	ASCII	"H3"
	WORD	8074H
	ASCII	"L3"
	WORD	8076H
	ASCII	"H4"
	WORD	8078H
	ASCII	"L4"
	WORD	807AH
	ASCII	"H5"
	WORD	807CH
	ASCII	"L5"
	WORD	807EH
	ASCII	"H6"
	WORD	8080H
	ASCII	"L6"
	WORD	8082H
	ASCII	"UH"
	WORD	8084H
	ASCII	"UL"
	WORD	8086H
	ASCII	"LH".
	WORD	8088H
	ASCII	"LL"
	WORD	808AH
	ASCII	"P1"
	WORD	808CH
	ASCII	"P2"
	WORD	808EH
	ASCII	"P3"
	WORD	8090H
	ASCII	"M1"
	WORD	8096H

	ASCII	"M2"
	WORD	8098H
	ASCII	"M3"
	WORD	809AH
	ASCII	"I1"
	WORD	809CH
	ASCII	"I2"
	WORD	809EH
	ASCII	"I3"
	WORD	80A0H
	ASCII	"PS"
	WORD	80A4H
	ASCII	"ES"
	WORD	80A6H
	ASCII	"TR"
	WORD	80A8H
	ASCII	"NS"
	WORD	80AAH
	ASCII	"KI"
	WORD	80B0H
	ASCII	"TS"
	WORD	80BCH
	ASCII	"PL"
	WORD	80BEH
	ASCII	"ET"
	WORD	80C4H
	ASCII	"NR"
	WORD	80CAH
	ASCII	"PR"
	WORD	80CCH
	ASCII	"EP"
	WORD	80D4H
	ASCII	"D1"
	WORD	80D6H
	ASCII	"D2"
	WORD	80D8H
	ASCII	"D3"
	WORD	80DAH
	ASCII	"D4"
	WORD	80DCH
	ASCII	"D5"
	WORD	80DEH
	ASCII	"D6"
	WORD	80EOH
STABE	EQU	\$
;		
QMSG	BYTE	CR, LF, "?", CR
PMSG	BYTE	CR, LF, ">", EOT
CUMSG	ASCII	"`U"
DDCS	ASCII	"D8040 805E"
	BYTE	CR, 0

```
TTYSETUP WORD      WP2
          WORD      $+2
          CLR       R3
          CLR       R4
          LI        R12,TTYBASE
          BL        @PROMPT
RTWP
ZZZ      EQU      $
;
;
SECTION INTHRWM,ABSOLUTE
ORG     8100H
RCBUFF  BLOCK    16
TXBUFF  BLOCK    50
END
```

## **APPENDIX E (cont.)**

```

START    LIMI    0          ; DISABLE INTERRUPTS
        LI      R12,ATOD   ; A/D BASE ADDRESS
        SBZ    MPXEN    ; ENABLE LOW
        SBO    ADSC     ; START CONVERT HIGH
        SBZ    SHMD     ; MODE LOW

; SET UP D TO A
;

DA1      EQU     0100H    ; BASE OF D/A 1
DA2      EQU     0140H    ; BASE OF D/A 2
DA3      EQU     0180H    ; BASE OF D/A 3
BVH      EQU     28       ; CRU BIT BAT V HIGH
DALSBB  EQU     16       ; PORT OF LSB
PULSE    EQU     28       ; PULSE BIT CRU POSITION
TFLAG    EQU     29       ; TRIP FLAG (TR RELAYS HAVE TRIPPED)
V15      EQU     5        ; 15 VOLT SENSE
;

LI      R12,DA1    ; D/A BASE ADDRESS
SBO    1          ; ENABLE ONE INTERRUPT FOR TTY
;

SBZ    PULSE    ; ZERO PULSE
SBZ    TFLAG    ; ZERO TRIP FLAG
SETO   RO       ; ALL ONES
LI      R12,DA1+(DALSBB*2) ; BASE FOR DIGITAL DATA
LDCR   RO,12    ; OUTPUT ALL ONES TO D/A
;

LI      R1,0700H  ; OTHER 2 D/AS
LI      R12,DA2+(DALSBB*2)
LDCR   RO,12    ; BUS OVERVOLTAGE AND HEATER TAPE
LI      R12,DA2+(BVH*2)
LDCR   R1,4     ; AND HEATER TAPE
LI      R12,DA3+(DALSBB*2)
LDCR   RO,12    ; ADDRESS OF 9902
LI      R12,DA3+(BVH*2)
LDCR   R1,4

; SETUP VDT CONTROL (9902)
;

RTRATE  EQU     209      ; RECEIVE AND TRANSMIT RATE
; (WITH 2 MHZ CLOCK)
CNTWD   EQU     0E200H   ; CONTROL WORD (MOST SIG BYTE)
TTYBASE EQU     00COH    ; ADDRESS OF 9902
;

LI      R12,TTYBASE  ; 9902 BASE ADDRESS
LI      RO,CNTWD
LI      R1,RTRATE
SBO    31       ; RESETS 9902
LDCR   RO,8     ; OUTPUT CNT WD, RESETS LDCTRL

```

```

        SBZ      13          ; NOTHING INTO INTERVAL
                    REGISTER
        LDCR     R1,12        ; DATA RATE, ALSO SETS
                    ALL INTERNAL
                    ; FLAGS...READY TO GO
        SBO      18          ; ENABLES 9902 RCV INT

;
; SET UP CCC WATCHER AND POWER SUPPLY CONTROL
;
CCCIN    EQU      40H          ; ADDRESS OF CCC INPUTS
POUT     EQU      80H          ; ADDRESS OF POWER
                    SUPPLY OUTPUTS
CCCLSB    EQU      1
POUTLSB   EQU      16
LI       R12,POUT+(POUTLSB*2) ;FOR OUTPUT, DONT
                    NEED INPUT
                    CLR      R1          ; ALL OS
                    LDCR     R1,13

;
; INITIALIZE ALL PARAMETERS
;
DIN      EQU      1          ; INITIAL DELTA
ITD      EQU      88H          ; INITIAL TIME DELAY
H1I      EQU      0CA9H        ; INITIAL DIODE TRIP POINT HIGH
L1I      EQU      0C05H        ; INITIAL DIODE TRIP POINT LOW
H2I      EQU      0F99H        ; INITIAL DIODE TRIP POINT HIGH
L2I      EQU      0ECCH        ; INITIAL DIODE TRIP POINT LOW
H3I      EQU      0F99H        ; INITIAL DIODE TRIP POINT HIGH
L3I      EQU      0ECCH        ; INITIAL DIODE TRIP POINT LOW
H4I      EQU      0F99H        ; INITIAL DIODE TRIP POINT HIGH
L4I      EQU      0ECCH        ; INITIAL DIODE TRIP POINT LOW
H5I      EQU      0F99H        ; INITIAL DIODE TRIP POINT HIGH
L5I      EQU      0ECCH        ; INITIAL DIODE TRIP POINT LOW
H6I      EQU      0F99H        ; INITIAL DIODE TRIP POINT HIGH
L6I      EQU      0ECCH        ; INITIAL DIODE TRIP POINT LOW
UHI     EQU      2ABH        ; INITIAL PLATE TEMPS TOP HIGH
ULI     EQU      290H        ; UPPER LOW
LHI     EQU      2ABH        ; LOWER HIGH
LLI     EQU      290H        ; LOWER LOW
APRV1I   EQU      410         ; INITIAL GUESS FOR PRVS (10 A)
APRV2I   EQU      410
APRV3I   EQU      410
P1I      EQU      733         ; 731W INITIAL
P2I      EQU      717
P3I      EQU      733
M1I      EQU      0E66H
M2I      EQU      0E66H
M3I      EQU      0E66H
I1I      EQU      1229        ; 30 AMPS (LOAD BANK I, 15/BATT)
I2I      EQU      1229
I3I      EQU      1229
PSI      EQU      0           ; POWER SUPPLY CONTROL
TRI      EQU      1           ; NO. OF TRIPS BEFORE P.S.
                    SHUTOFF

```

NSI	EQU	8	; TOTAL NO. OF SPAS OFF AT TR=CCC TRIPS
TSI	EQU	OFFFH	; MAX AVG TEMP ON PLATES
PLI	EQU	50	; CYCLES BETWEEN PULSES
TRFI	EQU	0	; TRIP BACK FLAG
DNFI	EQU	0	; DAY NIGHT FLAG
ETI	EQU	14	
ETCCI	EQU	100H	
EPI	EQU	325	
D1I	EQU	50	; DELTA POWER FOR ADD FIRST TIME OUT
D2I	EQU	50	; DELTA POWER FOR SUB SECOND TIME OUT
D3I	EQU	83	; DELTA....
D4I	EQU	83	
D5I	EQU	67	
D6I	EQU	67	
;			
;			
;	MACRO	WINIT	; MACRO DEFINITION
;	LI	RO,'1'	
;	MOV	RO,@'2'	
;	ENDM		
;			
;			
WINIT		DIN,DE	
WINIT		ITD,TDLY	
WINIT		H1I,H1	
WINIT		L1I,L1	
WINIT		H2I,H2	
WINIT		L2I,L2	
WINIT		H3I,H3	
WINIT		L3I,L3	
WINIT		H4I,H4	
WINIT		L4I,L4	
WINIT		H5I,H5	
WINIT		L5I,L5	
WINIT		H6I,H6	
WINIT		L6I,L6	
WINIT		UHI,UH	
WINIT		ULI,UL	
WINIT		LHI,LH	
WINIT		LLI,LL	
WINIT		APRV1I,APRV1	
WINIT		APRV2I,APRV2	
WINIT		APRV3I,APRV3	
WINIT		P1I,P1	
WINIT		P2I,P2	
WINIT		P3I,P3	
WINIT		M1I,M1	
WINIT		M2I,M2	
WINIT		M3I,M3	
WINIT		I1I,I1	
MOV		RO,@I2	

MOV	RO, @I3	
WINIT	PSI, PS	
MOV	RO, @ES	
MOV	RO, @TRF	
MOV	RO, @DNF	
MOV	RO, @KI	
MOV	RO, @LBCNT	
MOV	RO, @PR	
MOV	RO, @EPC	
MOV	RO, @EPCC	
WINIT	TRI, TR	
MOV	RO, @NEWRF	
WINIT	EPI, EP	
WINIT	D1I, D1	
WINIT	D2I, D2	
WINIT	D3I, D3	
WINIT	D4I, D4	
WINIT	D5I, D5	
WINIT	D6I, D6	
WINIT	NSI, NS	
WINIT	TSI, TS	
WINIT	PLI, PL	
MOV	RO, @PLC	
WINIT	ETI, ET	
WINIT	ETCCI, ETCC	
;		
BLWP	@TTYSETUP	; GO SETUP TTY WORKSPACE AND ; PUT OUT PROMPT
LIMI	1	; ENABLE INTERRUPTS
;		
;		
;		
SAMPLE ROUTINE		
;		
SAMPLE	LI	R2, CHLO ; CHANNEL 0 STORAGE ADDRESS
	LI	R1, 0016 ; COUNTER
	CLR	RO ; ADDR OF MPX ANALOG INPUT
SAMPLOOP	LI	R12, MPXAL*2 ; BASE OF MPX ADDR
	SLA	RO, 8 ; GET TO MSB FOR LDCR
	LDCR	RO, 4 ; SEND OUT ADDR
	SRL	RO, 8 ; GET BACK FOR INC
	LI	R12, ATOD ; BASE
	LIMI	0 ; MUST DISABLE INTERRUPTS
	SBO	MPXEN ; ENABLE MPX
	SBO	SHMD ; SAMPLE
	SBO	SHMD ; WAIT
	SBZ	SHMD ; HOLD
	SBZ	MPXEN ; DISABLE MPX
	SBZ	ADSC ; START CONVERSION
	SBO	ADSC ; PROCESS
NOTEOC	TB	ADEOC ; SEE IF THROUGH

```

JEQ      NOTEOC          ;NO, WAIT
LI       R12,ADLSB*2      ; BASE OF ADLSB
STCR    R4,12; GET DIGITAL DATA
LIMI    1                 ; ENABLE INTERRUPTS
INV     R4                 ; A/D INVERTING TYPE
ANDI    R4,OFFFH          ; STRIP LEADING ONES
                           FROM INV
MOV     R4,*R2+            ; STORE INVERTED DATA
INC     R0                 ; INC ADDR OF MPX
DEC     R1                 ; DEC COUNTER
JNE     SAMPLOOP          ; DO 16 TIMES
; CORRECT CHLS 1-9 WITH CHLO (OFFSET).
;

LI       R1,0
LI       R2,CHL1
CLOOP   S     @CHLO,*R2
JGT     NNEG
CLR     *R2
NNEG   INCT   R2
DEC     R1
JNE     CLOOP
;

; FIRST OF ALL, SEE IF IN TRICKLE CHARGE/CAP TEST (CONSTANT
; CURRENT DISCHARGE MODE) (KI = 1). IF SO AND IN NIGHT
; THEN PRVS = I1,I2,I3. IF IN DAY THEN DO THIS...
; IF (VB1+VB2)/2>M1 THEN PRV1=2048 (APRVS INC SLOWLY IN
OUTPRV)
; ELSE PRV1=0. SAME FOR 3-4, AND 5-6.
;

MOV     @KI,@KI
JEQ     CLOAD
LI      R12,DA1
TB      4                 ; DAY/NIGHT FLAG HERE
JEQ     TRC
MOV     @I1,@PRV1
MOV     @I2,@PRV2
MOV     @I3,@PRV3
B      OUTPRV
TRC   LI      R2,2048
      MOV     @VB1,R1
      A      @VB2,R1
      SRL    R1,1             ; DIVIDE BY 2
      C      R1,@M1
      JLT    ZPRVI
      MOV     R2,@PRV1
      JMP    CKV3V4
ZPRV1  CLR    @PRV1
      MOV     @VB3,R1
      A      @VB4,R1
      SRL    R1,1
      C      R1,@M2
      JLT    ZPRV2
      MOV     R2,@PRV2
      JMP    CKV5V6
CKV3V4

```

```

ZPRV2    CLR      @PRV2
CKV5V6   MOV      @VB5,R1
          A       @VB6,R1
          SRL      R1,1
          C       R1,@M3
          JLT      ZPRV3
          MOV      R2,@PRV3
          JMP      OUTPRV
ZPRV3    CLR      @PRV3
          JMP      OUTPRV
;
; CALCULATE V TO OUTPUT TO LOAD BANKS AT .1V/AMP
; P1,P2,P3 = EACH LB POWER DESIRED; VLB1,VLB2,VLB3=
; EACH LB VOLTAGE RANGED 0-40V (CHL1,2,3, 0-10V IN)
; EQUATION IS:
; P1(,2,3)*4095/VLB1(,2,3)*4095/4000 WHERE VLB1(,2,3)>
; 63 (MIN VOLTAGE FOR 32 BITS AT 1000W) AND FINAL
; ANSWER < 2048 (MAX INPUT TO LOAD BANKS)
;
CLOAD    LI       R3,4095
          LI       R4,4000
          MOV     @P1,R1           ; POWER DESIRED
          CI      R1,0
          JEQ     CON2
          MOV     @VLB1,R5          ; SAMPLED VOLTAGE
          BL      @CALC             ; TO CALCULATE
CON2     MOV     R1,@PRV1          ; STORE IT
          MOV     @P2,R1
          CI      R1,0
          JEQ     CON3
          MOV     @VLB2,R5
          BL      @CALC
CON3     MOV     R1,@PRV2
          MOV     @P3,R1
          CI      R1,0
          JEQ     CON4
          MOV     @VLB3,R5
          BL      @CALC
CON4     MOV     R1,@PRV3
          JMP     OUTPRV
CALC     MOV     @TRF,R7
          JNE     CALCC
          MOV     @PR,R7
          JEQ     CALCC
          MOV     @EPCC,R7
          JEQ     TEPC
          DEC     @EPCC
          JMP     LBRT1
TEPC     MOV     @EPC,R7
          JEQ     LBRT
          DEC     @EPC
          JMP     LBRT2
LBRT     INC     @LBCNT
          MOV     @EP,@EPC

```

LBRT2	LI	R7, ETCCI	
	MOV	R7, @EPCC	
LBRT1	MOV	@LBCNT, R7	
	CI	R7, 1	
	JNE	CLBCNT1	
	MOV	@D1, R8	
	JMP	CALCCA	
CLBCNT1	CI	R7, 2	
	JNE	CLBCNT2	
	MOV	@D2, R8	
	JMP	CALCCS	
CLBCNT2	CI	R7, 3	
	JNE	CLBCNT3	
	MOV	@D3, R8	
	JMP	CALCCA	
CLBCNT3	CI	R7, 4	
	JNE	CLBCNT4	
	MOV	@D4, R8	
	JMP	CALCCS	
CLBCNT4	CI	R7, 5	
	JNE	CLBCNT5	
	MOV	@D5, R8	
	JMP	CALCCA	
CLBCNT5	CI	R7, 6	
	JNE	CALCC	
	MOV	@D6, R8	
CALCCS	S	R8, R1	
	JMP	CALCC	
CALCCA	A	RI, R1	
CALCC	CI	R5, 63	; SEE IF TOO LOW
	JLT	ZERO1	; IF SO, PRV=0
	CI	R1, 1000	; 1000W MAX
	JLT	CON1	
	LI	R1, 1000	
CON1	MPY	R3, R1	
	DIV	R5, R1	
	MPY	R3, R1	
	DIV	R4, R1	
	JMP	FCALC	
ZERO1	CLR	R1	
FCALC	B	*R11	
OUTPRV	LI	R1, 2048	
	C	@PRV1, @APRV1	
	JEQ	RV2	
	JGT	INCP1	
	C	@APRV1, @DE	
	JLE	RV2	
	S	@DE, @APRV1	
	JMP	RV2	
INCP1	A	@DE, @APRV1	

```

        C          @APRV1,R1           ; SEE IF TOO BIG
        JLT RV2
        MOV
        C          R1,@APRV1
        JEQ
        JGT
        C          @PRV2,@APRV2      ; ETC 3 TIMES
        RV3
        INC P2
        C          @APRV2,@DE
        JLE
        RV3
        S          @DE,@APRV2
        JMP
        RV3
        INCP2
        A          @DE,@APRV2
        C          @APRV2,R1
        JLT
        RV3
        MOV
        C          @PRV3,@APRV3
        JEQ
        JGT
        C          @APRV3,@DE
        JLE
        OUTP
        RV3
        S          @DE,@APRV3
        JMP
        OUTP
        INCP3
        A          @DE,@APRV3
        C          @APRV3,R1
        JLT
        OUTP
        MOV
        R1,@APRV3

;
; IF STATUS OFF (EXT SWITCH TO GND)
; THEN ALL OUTPUTS TO 0
;

        OUTP
        LI          R12,DA1           ; BASE FO DIGITAL INPUT
        TB          3                 ; CRU ADDR OF SW
        JEQ
        COUTP
        CLR
        @APRV1
        CLR
        @APRV2
        CLR
        @APRV3
        SETO
        R1          ; ALL 1S
        LI          R12,DA1+(DALSB*2) ; BASE OF FIRST PRV,
                                ; ETC 3 TIMES
        LDCR
        LI          R1,12
        LDCR
        LI          R12,DA2+(DALSB*2)
        LDCR
        LI          R1,12
        LDCR
        LI          R12,DA3+(DALSB*2)
        LDCR
        R1,12
        JMP
        CKVBS
        MOV
        @APRV1,R1
        INV
        R1
        LI
        R12,DA1+(DALSB*2)
        LDCR
        R1,12
        MOV
        @APRV2,R1
        INV
        R1
        LI
        R12,DA2+(DALSB*2)
        LDCR
        R1,12
        MOV
        @APRV3,R1
        INV
        R1

```

```

LI      R12,DA3+(DALSBB*2)
LDCR    R1,12
;
; IF ANY TWO DIODE BUSSES > H1 THEN OPEN RELAYS
; (ADD DIODES).
; IF ANY TWO DIODE BUSSES < L1 THEN CLOSE RELAYS.
;
CKVBS   LI      R12,DA2+BVH*2
        CLR    R1
        CLR    R2
        C      @VLB1,@H1
        JLT    CKB2H
        INC    R1
CKB2H   C      @VLB2,@H1
        JLT    CKB3H
        INC    R1
CKB3H   C      @VLB3,@H1
        JLT    CKR1H
        INC    R1
CKR1H   CI     R1,2
        JLT    CKB1L
        LDCR   R2,3
        LI     R12,DA3+BVH*2
        LDCR   R2,3
CKB1L   LI     R12,DA2+BVH*2
        CLR    R1
        SETO   R2
        C      @VLB1,@L1
        JGT    CKB2L
        INC    R1
CKB2L   C      @VLB2,@L1
        JGT    CKB3L
        INC    R1
CKB3L   C      @VLB3,@L1
        JGT    CKR1L
        INC    R1
CKR1L   CI     R1,2
        JLT    DOTEMP
        LDCR   R2,3
        LI     R12,DA3+BVH*2
        LDCR   R2,3
;
; AVERAGE 3 EACH THERMISTOR ON EACH PLATE
; (UPPER AND LOWER), IF > UH (OR LH) THEN TURN
; OFF HEATER, IF < UL (OR LL) THEN TURN ON HEATER.
; UH IS THE UPPER PLATE HIGH TEMP, LH IS THE LOWER PLATE HIGH
; TEMP.
; UL IS THE UPPER PLATE LOW TEMP, LL IS THE LOWER PLATE LOW
; TEMP.
;
DOTEMP  LI     R12,DA2
        LI     R3,3
        CLR    R1
        MOV    @T1,R2

```

	A	@T2,R2	
	A	@T3,R2	; SUM
	DIV	R3,R1	
	MOV	R1,R6	
	C	R1,@UH	
	JLT	CKLT	
	SBZ	BVH+3	; WAS TOO HIGH, OFF HEATER
CKLT	JMP	CKHB	
	C	R1,@UL	
	JGT	CKHB	
	SBO	BVH+3	; WAS TOO LOW, ON HEATER
CKHB	LI	R12,DA3	
	CLR	R1	
	MOV	@T4,R2	
	A	@T5,R2	
	A	@T6,R2	
	DIV	R3,R1	
	A	R1,R6	
	SRL	R6,1	
	MOV	R6,@TAVG	
	C	R1,@LH	
	JLT	CKLB	
	SBZ	BVH+3	
	JMP	TRRT	
CKLB	C	R1,@LL	
	JGT	TRRT	
	SBO	BVH+3	

;

; TRIP BACK ROUTINE

;

; TR IS NO. OF CCC TRIPS (CCCT) THAT OCCUR BEFORE  
; ANY POWER SUPPLIES ARE CUT OFF. IF TR = 0 THIS  
; ROUTINE IS SKIPPED.

;

; NS IS THE TOTAL NO. OF EQUIVALENT SPAS TAKEN OFF.  
; IF THE CCC DISCONNECTS A P.S. THEN THE OTHER P.S. FOR THAT  
; BATTERY IS LEFT ALONE. THE ROUTINE FIRST CHECKS IF IT CAN  
; REMOVE NS SPAS WITH THE REMAINING 1 SPA P.S.S BEGINNING  
; WITH THE 1 SPA P.S. RIGHT AFTER THE BATTERY (OR THE FIRST  
; ONE IT SEES) THAT THE CCC CUT OFF. IF IT CAN IT DOES, ELSE  
; IT GOES BACK, ADDS THE ONE SPA P.S. AND TAKES OUT THE 2 SPA  
; P.S. (ALL THIS IS CHECKED BEFORE ANY ARE ACTUALLY SHUT OFF)  
; ONCE THE ROUTINE CUTS OFF THE P.S.(S), IT DOESNT CHECK  
; ANYMORE.

;

; POWER SUPPLIES CAN BE COMMANDED OFF BY SETTING THE  
; PARAMETER "PS" IN BINARY (YOU FIGURE THE HEX INPUT TO THE  
; TTY)

; ANY "1" IN THE WORD MEANS "OFF".  
; IN CASE YOU MESS UP AND TURN OFF TOO MANY IN THE ROUTINE,  
; P.S.S CAN BE TURNED BACK ON THIS DAY ONLY BY SETTING THE  
; PARAMETER "ES". ANY "ONE" MEANS ON.

```

; THE FORMAT IS ES,B6K2,B6K1,B5K2,B5K1,...,B2K2,B2K1,B1K2,
; B1K1.(13 BITS)
; WHERE ES IS THE EXTRA 2 SPAS.
    MACRO      AND
    MOV        @'1',R7
    INV        R7
    MOV        @'2'(R2),R8
    INV        R8
    SOC        R7,R8
    INV        R8
    ENDM

;
TRRT      LI        R12,DA1
          TB        4
          JEQ       TODAY      ; 0 IF NIGHT, 1 IF DAY
          SETO     @PSOUT   ; ALL PSS OFF
          CLR      @ES       ; RESET THOSE THAT WERE
                               TURNED ON
          CLR      @STT      ; JUST IN CASE
          CLR      @TRF      ; RESET TRIP FLAG IF
                               NIGHT
          CLR      @DNF      ; DAY NIGHT FLAG TO 0
          SBZ      TFLAG     ; TRIP FLAG ALWAYS 0 IN
                               NIGHT
BACK      TODAY
          B         OUTPS    ; TO OUTPUT
          MOV      @DNF,@DNF  ; CHECK FLAG
          JNE      TETR      ; WAS SET, JUMP
          INC      @DNF      ; FIRST DAY CYCLE
          CLR      @CCCT     ; CCC TRIPS
          LI       R9,0FFFH   ; MASK
          MOV      R9,@SLTN   ; SLTN
          CLR      @TRF      ; TRIP BACK FLAG
          CLR      @STT
          CLR      @SPOFF
          CLR      @PSOUT
          JMP      BACK      ; FIRST TIME THROUGH GO
                               TO OUTPUT
TETR
          MOV      @TR,@TR    ; IF 0 GET OUT
          JEQ      BACK
          MOV      @TRF,@TRF  ; IF 1 GET OUT
          JEQ      MAJR
          MOV      @NEWRF,R0   ; GO TO NEW ROUTINE?
          JEQ      BACK
          B       NEWR

;
; MAJOR ROUTINE
;
MAJR      LI        R12,CCCIN+(CCCLSB*2)
          STCR    @STT,12   ; INPUT FROM CCC
          CLR     R2
          AND     STT,SLTN  ; IF 0, NOTHING CHANGED
          MOV     R8,@STTSLTN ; SAVE IT, IF 0 NOTHING
                               CHANGED
          JEQ     STEP6    ; JUMP AHEAD IN CASE TR

```

			CHANGED
	ANDI	R7,0FFH	; STRIP LEADING OS
	MOV	R7,@SLTN	; SAVE INVERTED STT
	CLR	R2	
CSPA	AND	STTSLTN,MB1	; SEE IF TRIP ON EACH BATTERY
	JEQ	NKTRB	; NO, JUMP
	AND	STTSLTN,B1S1	; SEE HOW MANY WENT
	JNE	SPO1	; IF 0, 2 WENT
SPO1	INC	@SPOFF	; IF NOT ZERO, 1 WENT
	INC	@SPOFF	
	INC	@CCCT	: COUNT TRIPS
NKTRB	INCT R2		
	CI	R2,12	
	JNE	CSPA	
STEP6	C	@TR,@CCCT	; IF TR > CCCT, NOT YET
	JGT	OUTPSB	
	INC	@TRF	; TIME TO DO IT
	CLR	@LBCNT	
	CLR	@EPCC	
	CLR	@EPC	
	LI	R12,DA1	
	SBO	TFLAG	; SIGNAL TRIPBACK
	MOV	@STT,@PSOUT	
	MOV	@NEWRF,R0	; NEW ROUTINE?
	JEQ	STEP7	
	MOV	@ET,@ETC	
	LI	R0,ETCCI	
	MOV	R0,@ETCC	
	B	NEWR	
STEP7	LI	R1,5	
	CLR	R2	
STEP8	AND	STT,MB1	; FIND ONE THAT CCC BID
	JNE	STEP9A	
	INCT	R2	; LOOK AGAIN 4 MORE TIMES OR...
	DEC	R1	
	JNE	STEP8	
	CLR	R2	; ONLY HERE IF B6
	JMP	STEP9	
STEP9A	INCT	R2	
STEP9	LI	R1,5	
	MOV	R2,R0	; SEE IF CAN TAKE OFF 1SPA PS
STEP10B	C	@NS,@SPOFF	
	JEQ	OUTPSB	
	JLT	OUTPSB	
	AND	PSOUT,MB1	
	JNE	STEP10A	; IF 0, CAN DO
	SOC	@B1S1(R2),@PSOUT	; OR INTO PSOUT WORD
	INC	@SPOFF	; INC NO. OF SPA OFF
STEP10A	DEC	R1	; SIX BATT?
	JEQ	STEP11A	
	INCT	R2	

```

        CI      R2, I2
        JNE    STEP10B
        CLR      R2
        JMP    STEP10B
STEP11A  MOV      R0, R2      ; IF HERE, HAVE TAKEN 1
                  OFF ALL
                  LI      R1, 5      ; BATT'S AND NOT ENOUGH
                                         YET
STEP11B  C       @NS, @SPOFF
        JEQ    OUTPSB
        JLT    OUTPSB
STEP12   AND    STT, MB1      ; SEE IF CCC DID IT, IF
                                         NOT, DO IT
                  JNE    STEP12B
                  SZC    @B1S1(R2), @PSOUT ; PUT SINGLE SPA BACK
                  SOC    @B1S2(R2), @PSOUT ; TAKE OUT DOUBLE SPA
                  INC    @SPOFF
STEP12B  DEC      R1
        JEQ    OUTPSB      ; DONE 6 YET?
        INCT   R2
        CI      R2, 12
        JNE    STEP11B
        CLR      R2
        JMP    STEP11B
;
        OUTPSB  B      OUTPS      ; GET WITHIN RANGE
;
; NEW ROUTINE
; TAKE OFF 1 SPA EVERY X SECONDS (DETERMINED BY SETTING
; THE CAP ET) BEGINNING WITH BATTERY 1 AND GOING THROUGH
; ALL 6 UNTIL HAVE TAKEN OFF NS SPAS. THIS DOES NOT REMOVE
; ANY SPAS FROM A BATTERY WHOSE CCC TRIPPED OFF A POWER
; SUPPLY.
;
NEWR    DEC      @ETCC
        JNE    OUTPS
        DEC      @ETC
        JEQ    NEWRL1
        LI      R0, ETCCI
        MOV    R0, @ETCC
        JMP    OUTPS
NEWRL1  CLR      R2      ; TIME TO DO SOMETHING
        MOV    @ET, @ETC
        LI      R0, ETCCI      ; GETTING READY FOR
                                         NEXT TIME
;
        MOV    R0, @ETCC
        C       @NS, @SPOFF
        JEQ    OUTPS
        JLT    OUTPS
        AND    STT, MB1      ; IF 1, GO TO NEXT BATT
        JEQ    NEWRL3      ; IF 0, CHECK PSOUT FOR
                                         1 OR 2 SPAS
        INCT   R2
        CI      R2, 12

```

```

        JEQ      OUTPS
        JMP      NEWRL2
NEWRL3   AND      PSOUT,B1S2      ; IF NOT 0, 2 SPA IS
                ; ALREADY OUT
        JNE      NEWRL5      ; GO TO NEXT BATTERY
        AND      PSOUT,B1S1      ; IF 0, TAKE OUT 1 SPA
        JNE      NEWRL4      ; AND GET OUT
        SOC      @B1S1(R2),@PSOUT
        INC      @SPOFF
        JMP      OUTPS
NEWRL4   SZC      @B1S1(R2),@PSOUT      ; PUT 1 SPA BACK
        SOC      @B1S2(R2),@PSOUT      ; REMOVE 2 SPA
        INC      @SPOFF
        JMP      OUTPS
NEWRL5   INCT    R2      ; GO TO NEXT BATTERY
        CI      R2,12
        JNE      NEWRL2

;
; TIME TO OUTPUT
; DONT TURN OFF THOSE THAT CCC TURNED OFF (STT)
; TURN OFF THOSE THAT ARE FLAGGED BY "PS"
; TURN ON THOSE THAN ARE FLAGGED BY "ES" (RESET EACH ORBIT)
;

OUTPS   MOV      @PSOUT,R1
        SZC      @STT,R1      ; DONT TURN OFF IF CCC
                            ; OPENED
        SOC      @PS,R1      ; TURN OFF THOSE
                            ; FLAGGED BY "PS"
        SZC      @ES,R1      ; TURN ON THOSE
                            ; FLAGGED BY "ES"
        LI       R12,POUT+(POUTLSB*2)
        LDCR    R1,13

;
; TIME DELAY
;

TDLP    MOV      @TDLY,RO
TDLPL   DEC      RO
        JNE      TDLPL

;
; PULSE ROUTINE
; SHOULD PUT OUT PULSE EVERY SECOND SO NOT TO GET TIMEOUT
; ON ST HARDWARE. I.E., IF CC QUILTS, ST TEST SHUTS DOWN.
; A 60 US PULSE IS PUT OUT EVERY "PL" SOFTWARE CYCLES SO "TD"
; (TIME DELAY BETWEEN CYCLES) WILL HAVE AN EFFECT ALSO.
; THIS ALSO SENSES THE 15V SUPPLY AND STOPS PULSES IF IT
; FAILS. ALSO, IF THE AVERAGE OF THE SIX PLATE TEMPS
; EXCEEDS "TS", IT STOPS PULSES (CHAMBER FAIL HIGH TEMP)
; THIS ASSUMES THAT THE BATTERY HEATERS CAN KEEP THEM WARM
; IF THE CHAMBER FAILS LOW.
;

        LI       R12,DA1
        TB       V15
        JNE      OUTSAM
        C       @TAVG,@TS

```

```

JGT      OUTSAM
DEC      @PLC
JNE      OUTSAM
MOV      @PL, @PLC
LI       R1, 10
SBO      PULSE
TOL      DEC      R1
          JNE      TOL
          SBZ      PULSE
;
; END OF LOOP ..... SO DO FOREVER
;
OUTSAM  B       SAMPLE
MB1     WORD    11B, 1100B, 110000B, 11000000B, 1100000000B,
          110000000000B
B1S2    WORD    01B, 0100B, 010000B, 01000000B, 0100000000B,
          010000000000B
B1S1    WORD    10B, 1000B, 100000B, 10000000B, 1000000000B,
          100000000000B
ZZZ     EQU     $
;
;
SECTION TASKRWM, ABSOLUTE
;
ORG     RWM
;
WP1     BLOCK   32
WP2     BLOCK   32
;
;
CHL0    BLOCK   2           ; C0 EXAMINE
CHL1    BLOCK   2           ; C1
CHL2    BLOCK   2           ; ETC
CHL3    BLOCK   2
CHL4    BLOCK   2
CHL5    BLOCK   2
CHL6    BLOCK   2
CHL7    BLOCK   2
CHL8    BLOCK   2
CHL9    BLOCK   2
CHL10   BLOCK   2           ; CA
CHL11   BLOCK   2
CHL12   BLOCK   2
CHL13   BLOCK   2
CHL14   BLOCK   2
CHL15   BLOCK   2
PRV1    BLOCK   2           ; R1
PRV2    BLOCK   2           ; R2
PRV3    BLOCK   2           ; R3
APRV1   BLOCK   2           ; A1 EXAMINE AND SET
                            THE REST
APRV2   BLOCK   2           ; A2
APRV3   BLOCK   2           ; A3
H1      BLOCK   2

```

L1	BLOCK	2	
H2	BLOCK	2	
L2	BLOCK	2	
H3	BLOCK	2	
L3	BLOCK	2	
H4	BLOCK	2	
L4	BLOCK	2	
H5	BLOCK	2	
L5	BLOCK	2	
H6	BLOCK	2	
L6	BLOCK	2	
UH	BLOCK	2	
UL	BLOCK	2	
LH	BLOCK	2	
LL	BLOCK	2	
P1	BLOCK	2	
P2	BLOCK	2	
P3	BLOCK	2	
DE	BLOCK	2	
TDLY	BLOCK	2	; TD
M1	BLOCK	2	
M2	BLOCK	2	
M3	BLOCK	2	
I1	BLOCK	2	
I2	BLOCK	2	
I3	BLOCK	2	
PSOUT	BLOCK	2	
PS	BLOCK	2	
ES	BLOCK	2	
TR	BLOCK	2	
NS	BLOCK	2	
TRF	BLOCK	2	
DNF	BLOCK	2	
KI	BLOCK	2	
CCCT	BLOCK	2	
STT	BLOCK	2	
SLTN	BLOCK	2	
STTSLTN	BLOCK	2	
SPOFF	BLOCK	2	
TS	BLOCK	2	
PL	BLOCK	2	
PLC	BLOCK	2	
TAVG	BLOCK	2	
ET	BLOCK	2	
ETC	BLOCK	2	
ETCC	BLOCK	2	
NEWRF	BLOCK	2	
PR	BLOCK	2	; FLAG TO DO POWER STEP ROUTINE
EPC	BLOCK	2	
EPCC	BLOCK	2	
LBCNT	BLOCK	2	
EP	BLOCK	2	; WHICH STEP ; COUNTER INITIAL VALUE

```

D1      BLOCK    2          ; FIRST POWER DELTA
D2      BLOCK    2          ; (ADD)
D3      BLOCK    2          ; SECOND POWER DELTA
D4      BLOCK    2          ; (SUB)
D5      BLOCK    2          ; THIRD..ETC...
D6      BLOCK    2

;
;

VLB1    EQU      CHL1
VLB2    EQU      CHL2
VLB3    EQU      CHL3
VB1     EQU      CHL4
VB2     EQU      CHL5
VB3     EQU      CHL6
VB4     EQU      CHL7
VB5     EQU      CHL8
VB6     EQU      CHL9
T1      EQU      CHL10
T2      EQU      CHL11
T3      EQU      CHL12
T4      EQU      CHL13
T5      EQU      CHL14
T6      EQU      CHL15
;

;

END      START

```

## **APPROVAL**

### **HUBBLE SPACE TELESCOPE SIX-BATTERY TEST BED**

By J.A. Pajak, J.R. Bush, Jr., and J.R. Lanier, Jr.

The information in this report has been reviewed for technical content. Review of any information concerning Department of Defense or nuclear energy activities or programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

  
Joseph L. Randall  
JOSEPH L. RANDALL  
Director, Information and Electronic Systems Laboratory





